

TESLA TT26EX21-0932IA



FEATURES

4-Fan Speed: Low/Middle/High/Turbo, 3D Air Flow: Vertical/Horizontal Auto Swing, Turbo Mode, Anti-cold Air, I Feel, Low Temperature Heating/Cooling -15°C, Comfortable Cooling, Independent Dehumidification, Auto mode, Display On/OFF, smart airflow, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Anti-rust proo cabinet, Wide Voltage Range Start-up, Strong Cooling at 60°C, Leakage Detection, Auto-restart, Self-diagnosis, Louver Position Memory, Dual drainage, Washable filter, Hidden Display, Self-cleaning, Refrigerant Leak Detection, Sleep Mode, ECO function, Timer

| | | | |
|---|---|-----------------------|-------------------------------------|
| Capacity | | | 9000BTU |
| Rated volt and frequency | | V/Hz | 220-240V~/50HZ |
| Mode | | | Cooling Heating |
| Rated capacity | | W | 2600 (940~3300) 2610(940~3360) |
| Power input | | W | 750 752 |
| Current input | | A | 4.60 4.10 |
| SEER-SCOP/ Energy Class | | W/W | 6,3/ A++ 4,0/A+ |
| Operating range | | (°C) | 0 - 53°C -20°C - 30°C |
| Energy consumption (per year, based on standard test results) | | kwh | 144 735 |
| Dehumidifying | | Kg/h | 0.9 |
| Degree of protection (IN) / (OUT) | | (IP) | IPX4/IPX4 |
| Class of electric protection (IN) / (OUT) | | Class I / Class II | I/I |
| Max. input consumption | | W | 1040 |
| Max. current | | A | 4.8 |
| Compressor | | Model | KSN98D32UEZ |
| | | Type | Rotary |
| | | Brand | GMCC |
| Indoor | Fan motor | Model | 1170030067G |
| | | Power input | W 20W output |
| | | Capacity | uF 1.5 |
| | | Indoor Fan Speed RPM | r/min ≤1320 |
| | Indoor fan | Dia. / Length | mm φ92×578 |
| | Indoor Air Circulation | | m³/h 420 |
| | Indoor Noise Level dB | | dB(A) 32/35/43/50 |
| | Net Dimension (L×W×H) | | mm 693×190×255 |
| | Packing Dimension (L×W×H) | | mm 777×332×270 |
| | Net Weight/Gross Weight | | Kg 6,5/7,9 |
| Outdoor | Fan motor | Model | 1170040162AB |
| | | Power input | W 33W output |
| | | Capacity | uF / |
| | | Outdoor Fan Speed RPM | r/min ≤1000 |
| | Outdoor fan | Length | mm φ384×134 |
| | Outdoor Noise Level dB | | dB(A) 22/25/33/40/60 |
| | Net Dimension (L×W×H) | | mm 777×290×495 |
| | Packing Dimension (L×W×H) | | mm 822×335×530 |
| | Net Weight/Gross Weight | | Kg 24,0/25,5 |
| | Refrigerant type/weight | | g R32/530/675 |
| Max. Discharge/Max. Suction pressure | | Mpa 3.7/1.2 | |
| Refrigerant piping | Liquid side / Gas side | | mm 6,35/9,52 |
| | Max. refrigerant pipe length / Max. difference in level | | m 25/10 |