

TESLA TT26EX81-0932IAW



FEATURES

4-Fan Speed: Low/Middle/High/Turbo, 3D Air Flow: Vertical/Horizontal Auto Swing, Turbo Mode, Anti-cold Air, I Feel, Low Temperature Heating/Cooling -15°C, Comfortable Cooling, Independent Dehumidification, Auto mode, Display On/OFF, smart airflow, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Anti-rust proo cabinet, Wide Voltage Range Start-up, Strong Cooling at 60°C, Leakage Detection, Auto-restart, Self-diagnosis, Louver Position Memory, Dual drainage, Washable filter, Hidden Display, Self-cleaning, Refrigerant Leak Detection, Sleep Mode, ECO function, Timer, WIFI

Capacity			9000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	2600 (940~3300) 2610(940~3360)	
Power input		W	750 752	
Current input		A	4.60 4.10	
SEER-SCOP/ Energy Class		W/W	6,3/ A++ 4,0/A+	
Operating range		(°C)	0 - 53°C -20°C - 30°C	
Energy consumption (per year, based on standard test results)		kwh	144 735	
Dehumidifying		Kg/h	0.9	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/II	
Max. input consumption		W	1040	
Max. current		A	4.8	
Compressor		Model	KSN98D32UEZ	
		Type	Rotary	
		Brand	GMCC	
Indoor	Fan motor	Model	1170030067G	
		Power input	W 20W output	
		Capacity	uF 1.5	
		Indoor Fan Speed RPM	r/min ≤1320	
	Indoor fan	Dia. / Length	mm φ92×578	
	Indoor Air Circulation		m³/h	420
	Indoor Noise Level dB		dB(A)	32/35/43/50
	Net Dimension (L×W×H)		mm	693×190×255
	Packing Dimension (L×W×H)		mm	777×332×270
	Net Weight/Gross Weight		Kg	6,5/7,9
Outdoor	Fan motor	Model	1170040162AB	
		Power input	W 33W output	
		Capacity	uF /	
		Outdoor Fan Speed RPM	r/min ≤1000	
	Outdoor fan	Length	mm φ384×134	
	Outdoor Noise Level dB		dB(A)	22/25/33/40/60
	Net Dimension (L×W×H)		mm	777×290×495
	Packing Dimension (L×W×H)		mm	822×335×530
	Net Weight/Gross Weight		Kg	24,0/25,5
	Refrigerant type/weight		g	R32/530/675
Max. Discharge/Max. Suction pressure		Mpa	3.7/1.2	
Refrigerant piping	Liquid side / Gas side		mm	6,35/9,52
	Max. refrigerant pipe length / Max. difference in level		m	25/10