

TESLA TT34EX21-1232IA



FEATURES

4-Fan Speed: Low/Middle/High/Turbo, 3D Air Flow: Vertical/Horizontal Auto Swing, Turbo Mode, Anti-cold Air, I Feel, Low Temperature Heating/Cooling -15°C, Comfortable Cooling, Independent Dehumidification, Auto mode, Display On/OFF, smart airflow, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Anti-rust proo cabinet, Wide Voltage Range Start-up, Strong Cooling at 60°C, Leakage Detection, Auto-restart, Self-diagnosis, Louver Position Memory, Dual drainage, Washable filter, Hidden Display, Self-cleaning, Refrigerant Leak Detection, Sleep Mode, ECO function, Timer

Capacity				12000BTU
Rated volt and frequency			V/Hz	220-240V~/50HZ
Mode				CoolingHeating
Rated capacity			W	3400 (1000~3770)3420 (1000~3810)
Power input			W	1130922
Current input			A	5.804.70
SEER-SCOP/ Energy Class			W/W	6,1/ A++4,0/A+
Operating range			(°C)	0 - 53°C-20°C - 30°C
Energy consumption (per year, based on standard test results)			kwh	195840
Dehumidifying			Kg/h	1.2
Degree of protection (IN) / (OUT)			(IP)	IPX4/IPX4
Class of electric protection (IN) / (OUT)			Class I / Class II	I/I
Max. input consumption			W	1720
Max. current			A	10
Compressor		Model		KSN98D32UEZ
		Type		Rotary
		Brand		GMCC
Indoor	Fan motor	Model		1170030067G
		Power input	W	20W output
		Capacity	uF	2
		Indoor Fan Speed RPM	r/min	≤1320
	Indoor fan	Dia. / Length	mm	φ92×578
	Indoor Air Circulation		m³/h	550
	Indoor Noise Level dB		dB(A)	22/25/33/37/40
	Net Dimension (L×W×H)		mm	777×197×250
	Packing Dimension (L×W×H)		mm	850×320×263
	Net Weight/Gross Weight		Kg	8/9,8
	Outdoor	Fan motor	Model	
Power input			W	33W output
Capacity			uF	/
Outdoor Fan Speed RPM			r/min	≤1000
Outdoor fan		Length	mm	φ384×134
Outdoor Noise Level dB		dB(A)	29/33/39/46/50	
Net Dimension (L×W×H)		mm	777×290×495	
Packing Dimension (L×W×H)		mm	822×335×530	
Net Weight/Gross Weight		Kg	23,3/25,2	
Refrigerant type/weight		g	R32/550g/675	
Max. Discharge/Max. Suction pressure		Mpa	3.7/1.2	
Refrigerant piping		Liquid side / Gas side	mm	6.35/9.52
		Max. refrigerant pipe length / Max. difference in level	m	25/10