

## TESLA TT34EX81-1232IAW



### FEATURES

4-Fan Speed: Low/Middle/High/Turbo, 3D Air Flow: Vertical/Horizontal Auto Swing, Turbo Mode, Anti-cold Air, I Feel, Low Temperature Heating/Cooling -15°C, Comfortable Cooling, Independent Dehumidification, Auto mode, Display On/OFF, smart airflow, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Anti-rust proo cabinet, Wide Voltage Range Start-up, Strong Cooling at 60°C, Leakage Detection, Auto-restart, Self-diagnosis, Louver Position Memory, Dual drainage, Washable filter, Hidden Display, Self-cleaning, Refrigerant Leak Detection, Sleep Mode, ECO function, Timer, WIFI

<b>Capacity</b>			12000BTU	
<b>Rated volt and frequency</b>		V/Hz	220-240V~/50HZ	
<b>Mode</b>			<b>Cooling</b> <b>Heating</b>	
<b>Rated capacity</b>		W	3400 (1000~3770)                      3420 (1000~3810)	
<b>Power input</b>		W	1130    922	
<b>Current input</b>		A	5.80    4.70	
<b>SEER-SCOP/ Energy Class</b>		W/W	6,1/ A++    4,0/A+	
<b>Operating range</b>		(°C)	0 - 53°C    -20°C - 30°C	
<b>Energy consumption ( per year, based on standard test results)</b>		kwh	195    840	
<b>Dehumidifying</b>		Kg/h	1.2	
<b>Degree of protection (IN) / (OUT)</b>		(IP)	IPX4/IPX4	
<b>Class of electric protection (IN) / (OUT)</b>		Class I / Class II	I/II	
<b>Max. input consumption</b>		W	1720	
<b>Max. current</b>		A	10	
<b>Compressor</b>		Model	KSN98D32UEZ	
		Type	Rotary	
		Brand	GMCC	
<b>Indoor</b>	<b>Fan motor</b>	Model	1170030067G	
		Power input	W    20W output	
		Capacity	uF    2	
		Indoor Fan Speed RPM	r/min    ≤1320	
	Indoor fan	Dia. / Length	mm    φ92×578	
	Indoor Air Circulation		m³/h	550
	Indoor Noise Level dB		dB(A)	22/25/33/37/40
	Net Dimension (L×W×H)		mm	777×197×250
	Packing Dimension (L×W×H)		mm	850×320×263
	Net Weight/Gross Weight		Kg	8/9,8
<b>Outdoor</b>	<b>Fan motor</b>	Model	1170040162AB	
		Power input	W    33W output	
		Capacity	uF    /	
		Outdoor Fan Speed RPM	r/min    ≤1000	
	Outdoor fan	Length	mm    φ384×134	
	Outdoor Noise Level dB		dB(A)	29/33/39/46/50
	Net Dimension (L×W×H)		mm	777×290×495
	Packing Dimension (L×W×H)		mm	822×335×530
	Net Weight/Gross Weight		Kg	23,3/25,2
	Refrigerant type/weight		g	R32/550g/675
Max. Discharge/Max. Suction pressure		Mpa	3.7/1.2	
<b>Refrigerant piping</b>	Liquid side / Gas side		mm	6.35/9.52
	Max. refrigerant pipe length / Max. difference in level		m	25/10