

TESLA TT34EXC1-1232IAWPC



FEATURES

4-Fan Speed: Low/Middle/High/Turbo, 3D Air Flow: Vertical/Horizontal Auto Swing, Turbo Mode, Anti-cold Air, I Feel, Low Temperature Heating/Cooling -15°C, Comfortable Cooling, Independent Dehumidification, Auto mode, Display On/OFF, smart airflow, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Anti-rust proo cabinet, Wide Voltage Range Start-up, Strong Cooling at 60°C, Leakage Detection, Auto-restart, Self-diagnosis, Louver Position Memory, Dual drainage, Washable filter, Hidden Display, Self-cleaning, Refrigerant Leak Detection, Sleep Mode, ECO function, Timer, WIFI, Instalation kit.

Capacity			12000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			Cooling
Rated capacity		W	3400 (1000~3770)
Power input		W	1130
Current input		A	5.80
SEER-SCOP/ Energy Class		W/W	6,1/ A++
Operating range		(°C)	0 - 53°C
Energy consumption (per year, based on standard test results)		kwh	195
Dehumidifying		Kg/h	1.2
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	1720
Max. current		A	10
Compressor	Model		KSN98D32UEZ
	Type		Rotary
	Brand		GMCC
Indoor	Fan motor	Model	1170030067G
		Power input	20W output
		Capacity	2
		Indoor Fan Speed RPM	≤1320
	Indoor fan	Dia. / Length	φ92×578
	Indoor Air Circulation		m³/h
	Indoor Noise Level dB		22/25/33/37/40
	Net Dimension (L×W×H)		777×197×250
	Packing Dimension (L×W×H)		850×320×263
	Net Weight/Gross Weight		8/9,8
Outdoor	Fan motor	Model	1170040162AB
		Power input	33W output
		Capacity	/
		Outdoor Fan Speed RPM	≤1000
	Outdoor fan	Length	φ384×134
	Outdoor Noise Level dB		29/33/39/46/50
	Net Dimension (L×W×H)		777×290×495
	Packing Dimension (L×W×H)		822×335×530
	Net Weight/Gross Weight		23,3/25,2
	Refrigerant type/weight		R32/550g/675
Refrigerant piping	Max. Discharge/Max. Suction pressure		3.7/1.2
	Liquid side / Gas side		6.35/9.52
	Max. refrigerant pipe length / Max. difference in level		25/10