

## TESLA TT51TP21-1832IAWUV



### FEATURES

4-Fan Speed: Low/Middle/High/Turbo, 3D Air Flow: Vertical/Horizontal Auto Swing, Turbo Mode, Anti-cold Air, I Feel, Low Temperature Heating/Cooling -15°C, Comfortable Cooling, Independent Dehumidification, Auto mode, Display On/OFF, smart airflow, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Anti-rust proo cabinet, Wide Voltage Range Start-up, Strong Cooling at 60°C, Leakage Detection, Auto-restart, Self-diagnosis, Louver Position Memory, Dual drainage, Washable filter, Hidden Display, Self-cleaning, Refrigerant Leak Detection, Sleep Mode, ECO function, Timer, WIFI, UVC Sterilization.



<b>Capacity</b>			18000BTU
<b>Rated volt and frequency</b>		V/Hz	220-240V~/50HZ
<b>Mode</b>			<b>Cooling</b> <b>Heating</b>
<b>Rated capacity</b>		W	5100 (1250~5900)      5130 (1250~6080)
<b>Power input</b>		W	1579      1372
<b>Current input</b>		A	8.20      7.20
<b>SEER-SCOP/ Energy Class</b>		W/W	6,1/ A++      4,0/A+
<b>Operating range</b>		(°C)	-15°C - 53°C      -20°C - 30°C
<b>Energy consumption ( per year, based on standard test results)</b>		kwh	293      1373
<b>Dehumidifying</b>		Kg/h	1.8
<b>Degree of protection (IN) / (OUT)</b>		(IP)	IPX4/IPX4
<b>Class of electric protection (IN) / (OUT)</b>		Class I / Class II	I/II
<b>Max. input consumption</b>		W	2340
<b>Max. current</b>		A	13
<b>Compressor</b>		Model	C-6RZ146H3BAF
		Type	Rotary
		Brand	SANYO
<b>Indoor</b>	<b>Fan motor</b>	Model	210900495E
		Power input	W      25W output
		Capacity	uF      /
		Indoor Fan Speed RPM	r/min      ≤1350
	Indoor fan	Dia. / Length	mm      φ98×702
	Indoor Air Circulation		m³/h      820
	Indoor Noise Level dB		dB(A)      27/35/38/41/43/55
	Net Dimension (L×W×H)		mm      920×306×195
	Packing Dimension (L×W×H)		mm      990×382×266
	Net Weight/Gross Weight		Kg      okt.13
<b>Outdoor</b>	<b>Fan motor</b>	Model	GZSDJ-33(DC)
		Power input	W      40W output
		Capacity	uF      /
		Outdoor Fan Speed RPM	r/min      ≤1000
	Outdoor fan	Length	mm      φ439×154
	Outdoor Noise Level dB		dB(A)      36/43/47/50/54/65
	Net Dimension (L×W×H)		mm      853×602×349
	Packing Dimension (L×W×H)		mm      890×628×385
	Net Weight/Gross Weight		Kg      35/38
	Refrigerant type/weight		g      R32/920g
Max. Discharge/Max. Suction pressure		Mpa      3,7/1,2	
<b>Refrigerant piping</b>	Liquid side / Gas side		mm      6.35/12.7
	Max. refrigerant pipe length / Max. difference in level		m      25/10