

TESLA TT68EX21-2432IA



FEATURES

4-Fan Speed: Low/Middle/High/Turbo, 3D Air Flow: Vertical/Horizontal Auto Swing, Turbo Mode, Anti-cold Air, I Feel, Low Temperature Heating/Cooling -15°C, Comfortable Cooling, Independent Dehumidification, Auto mode, Display On/OFF, smart airflow, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Anti-rust proo cabinet, Wide Voltage Range Start-up, Strong Cooling at 60°C, Leakage Detection, Auto-restart, Self-diagnosis, Louver Position Memory, Dual drainage, Washable filter, Hidden Display, Self-cleaning, Refrigerant Leak Detection, Sleep Mode, ECO function, Timer

Capacity			24000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			Cooling Heating
Rated capacity		W	6810 (1830~7800) 6870(1850~7900)
Power input		W	2257 2063
Current input		A	10.70 9.90
SEER-SCOP/ Energy Class		W/W	6,1/ A++ 4,0/A+
Operating range		(°C)	0 - 53°C -20°C - 30°C
Energy consumption (per year, based on standard test results)		kwh	390 1680
Dehumidifying		Kg/h	2.4
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	2900
Max. current		A	13.5
Compressor		Model	ATN150D42UFZ
		Type	DC
		Brand	GMCC
Indoor	Fan motor	Model	GGSDJ-23A
		Power input	W 45W output
		Capacity	uF 3
		Indoor Fan Speed RPM	r/min ≤1280
	Indoor fan	Dia. / Length	mm φ111.5X1010
	Indoor Air Circulation		m³/h 1000/1100
	Indoor Noise Level dB		dB(A) 30/38/41/44/54
	Net Dimension (LxWxH)		mm 1010×315×220
	Packing Dimension (LxWxH)		mm 1096×390×297
	Net Weight/Gross Weight		Kg 13/15
Outdoor	Fan motor	Model	GZSDJ-31(DC)
		Power input	W 70W output
		Capacity	uF /
		Outdoor Fan Speed RPM	r/min ≤1000
	Outdoor fan	Length	mm φ536×153
	Outdoor Noise Level dB		dB(A) 47/51/55/58/67
	Net Dimension (LxWxH)		mm 968×655×375
	Packing Dimension (LxWxH)		mm 1015×715×425
	Net Weight/Gross Weight		Kg 40/43
	Refrigerant type/weight		g R32/1140/675
Max. Discharge/Max. Suction pressure		Mpa 3,7/1,2	
Refrigerant piping	Liquid side / Gas side	mm	6.35/15.88
	Max. refrigerant pipe length / Max. difference in level	m	25/10