

## TESLA TC61V3-24410IA

Inverter Split Type A Models



Funkcija protiv stvaranja gljivica, samo čišćenje, samo dijagnostika, odlične EMC karakteristike, nerđajuće kućište, samo otapanje, tihi dizajn, Turbo funkcija, režim spavanja, indikator greške, nizak nivo buke, sistem raspršivanja vazduha, dvostrani odvod za kondenz, više brzina ventilatora, automatsko restartovanje, tajmer, više vrsta filtracije vazduha,

## FUNKCIJE

<b>Kapacitet</b>		24000BTU	
<b>Napajanje (Ph-V-Hz)</b>		1-220-240/50	
<b>Režim rada</b>		<b>Hlađenje</b>   <b>Grejanje</b>	
<b>Nominalni kapacitet (W)</b>		6100W(1500W-6500W)   6100W(1800W-7000W)	
<b>Power input (W)</b>		1900W(400W-3000W)   1680W(450W-2300W)	
<b>Ulazna snaga (A)</b>		8.3A(1.8A-13.6A)   7.4A(2.0A-10.5A)	
<b>Working temperature</b>		-15 to 46 degree   -15 to 24 degree	
<b>SEER/SCOP (W/W)</b>		5.6/A++   4/A+	
<b>Climatic zones of heating</b>		/   Average	
<b>Design load (W)</b>		6100   5500	
<b>T biv. (°C) Heating balance point temperature</b>		/   -7	
<b>T ol. (°C) Heating limit operating temperature</b>		/   -10	
<b>Thermostat-off mode (W)</b>		70	
<b>Stand by mode (W)</b>		0,5	
<b>Throttle type</b>		Capillary	
<b>Annual consumption (KW)</b>		381   1925	
<b>(L/h) Moisture Removal</b>		2,21	
<b>Kompresor</b>	Model	ATD150RDPA8JT	
	Tip (Rotary, Piston, scroll)	Rotary	
	Brand	HIGHLY	
<b>Unutrašnja jedinica</b>	Motor ventilatora	Model	RPG50A-1
		Power type	AC
		Ulazna snaga (W)	85
		Capacitance (uF)	2,5
		Brzina RPM (High/Med/Low)	1350
	Protok vazduha (m <sup>3</sup> /h)	1050	
	Neto dimenzije (LxWxH) (mm)	1055×313×240	
Bruto dimenzije (LxWxH) (mm)	1258×400×328		
Neto / Bruto težina (Kg)	16/20		
Noise sound pressure level (dB/A)	42-48		
Sound power noise (dB/A)	52-58		
<b>Spoljašnja jedinica</b>	Motor ventilatora	Model	DR-9538-722A
		Power type	DC
		Ulazna snaga (W)	57
		Kapacitet (uF)	/
		Indoor Fan Speed RPM (High/Med/Low)	850
	Neto dimenzije (LxWxH) (mm)	850×295×605	
	Bruto dimenzije (LxWxH) (mm)	995×415×690	
	Neto / Bruto težina (Kg)	41/48	
	Noise sound pressure level (dB/A)	55	
	Sound power noise (dB/A)	65	
	Tip gasa / količina	R410A/1920g	
Defrost mode	Automatic defrosting		
Applicable climate types	T1		
<b>Cevi</b>	Tečna / gasna / dužina	φ6.0+φ12.0×5000	
	Maksimalna dužina / Visinska razlika	20/15	