

I FEEL

The remote control can keep track of the temperature at its current location and send the signal to the air conditioner, so it can optimize the room temperature for your maximum comfort.



Self-diagnostic

The air conditioner is able to monitor its operations and identify problematic or faulty parts. If they're found, the system will switch off automatically, while the error code will be displayed on the indoor unit.



Anti-fungus

The air conditioner will start the Anti-fungus feature after exiting cooling and dehumidifying mode. It helps prevent fungi and bacteria from spreading in order to maintain a healthy environment.



Noise-minimizing design

With an optimized operating mechanism, sound insulating materials for compressor, low-noise fan motor and ventilation structure that combines modern technology with aerodynamic design, this AC model minimizes noise levels while creating your perfect room temperature.



Turbo mode

When the air conditioner goes into Turbo mode, it will maximize its cooling or heating capacity, making the room cooler or warmer rapidly.



Auto cleaning

When this feature is activated, the indoor unit starts operating in cooling mode with a low fan speed, while the condensed water cleans dust from the evaporator fins. The AC then switches to heating with low fan speed, drying the inside of the indoor unit. Finally, it turns to fan-only mode and blows away the rest of the moisture. The whole process keeps the indoor unit dry and prevents bacterial growth.



Features

High density filter, Cold-catalyst filter, i-clean, low ambient kit(function), five speed outdoor fan motor, golden fin, refrigerant leakage detect, 8°C heating (frost protection), low noise airflow system (Silent), turbo operation, horizontal louver autoswing, follow me, Emergency Using (when temp sensor is abnormal), ECO, sleep mode, 1W standby, 2 ways piping connection, auto-restart, timer, π-shaped installation plate, louver position memory function, mono & multi compatible, I Remote (Engineering Mode), Intelligent dusting switch, breeze away

Capacity			9000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			CoolingHeating
Rated capacity		W	2367 (1025-3223)2930 (820-3369)
Power input		W	732733
Current input		A	3, 183, 18
SEER-SCOP/ Energy Class		W/W	6, 3/ A++4, 0/A+
Operating range		(°C)	15°C - 50°C-15°C - 24°C
Energy consumption (per year, based on standard test results)		kwh	
Dehumidifying		Kg/h	1,2
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	2150
Max. current		A	10
Compressor		Model	KSK103D33UEZ3(YJ)
		Type	Rotary
		Brand	GMCC
Indoor	Fan motor	Model	ZKFP-13-8-4
		Power input	W40W output
		Capacity	uF
		Indoor Fan Speed RPM	r/min700/900/1050
	Indoor fan	Dia. / Length	mmφ7
	Indoor Air Circulation		m³/h466
	Indoor Noise Level dB		dB(A)38.5/32/25
	Net Dimension (L×W×H)		mm805×194×285
	Packing Dimension (L×W×H)		mm870×270×365
	Net Weight/Gross Weight		Kg38633
Outdoor	Fan motor	Model	ZKFN-20-8-1
		Power input	W/
		Capacity	uF/
		Outdoor Fan Speed RPM	r/min800
	Outdoor fan	Length	mm815
	Outdoor Noise Level dB		dB(A)62
	Net Dimension (L×W×H)		mm720×270×495
	Packing Dimension (L×W×H)		mm835×300×540
	Net Weight/Gross Weight		Kg23.5/25.0
	Refrigerant type/weight		gR32/675g
	Max. Discharge/Max. Suction pressure		Mpa4,3/1.7
	Refrigerant piping		Liquid side / Gas side
Max. refrigerant pipe length / Max. difference in level			m25/10