

### I FEEL

The remote control can keep track of the temperature at its current location and send the signal to the air conditioner, so it can optimize the room temperature for your maximum comfort.



### Self-diagnostic

The air conditioner is able to monitor its operations and identify problematic or faulty parts. If they're found, the system will switch off automatically, while the error code will be displayed on the indoor unit.



### Anti-fungus

The air conditioner will start the Anti-fungus feature after exiting cooling and dehumidifying mode. It helps prevent fungi and bacteria from spreading in order to maintain a healthy environment.



### Noise-minimizing design

With an optimized operating mechanism, sound insulating materials for compressor, low-noise fan motor and ventilation structure that combines modern technology with aerodynamic design, this AC model minimizes noise levels while creating your perfect room temperature.



### Turbo mode

When the air conditioner goes into Turbo mode, it will maximize its cooling or heating capacity, making the room cooler or warmer rapidly.



### Auto cleaning

When this feature is activated, the indoor unit starts operating in cooling mode with a low fan speed, while the condensed water cleans dust from the evaporator fins. The AC then switches to heating with low fan speed, drying the inside of the indoor unit. Finally, it turns to fan-only mode and blows away the rest of the moisture. The whole process keeps the indoor unit dry and prevents bacterial growth.



## Features

I Feel / Follow me, ECO, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Intelligent dusting, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer, 4-Fan Speed, Five-speed outdoor fan, 12 grades indoor fan speed, Golden fin, Mono & multi compatibility, 8°C heating feature, Low-Temperature Heating/Cooling, Washable filter, High-density filter, Cold-catalyst filter, Super Ionizer, Low ambient kit, 1W Standby, Dual side Drainage, 3D Air Flow, Refrigerant Leakage Detect, Remote control, Louver position memory function, Horizontal louver auto-swing, Hidden led display, Display ON/OFF, RC holder, Hydrophilic Aluminum Fin, Backup Switch, Intelligent on-off, Auto Swing Louver function, Anti-Cold Air

|  |                                      |   |                   |
|--|--------------------------------------|---|-------------------|
| <b>Capacity</b>  |                                      |   | 9000BTU           |
| <b>Rated volt and frequency</b>                                      |                                      | V/Hz  | 220-240V~/50HZ    |
| <b>Mode</b>  |                                      |   | <b>Cooling</b>    |
| <b>Rated capacity</b>  |                                      | W   | 2367 (1025-3223)  |
| <b>Power input</b>   |                                      | W   | 732               |
| <b>Current input</b>   |                                      | A   | 3, 18             |
| <b>SEER-SCOP/ Energy Class</b>                                       |                                      | W/W   | 6, 3/ A++         |
| <b>Operating range</b>   |                                      | (°C)  | 15°C - 50°C       |
| <b>Energy consumption (per year, based on standard test results)</b> |                                      | kwh   |                   |
| <b>Dehumidifying</b>   |                                      | Kg/h  | 1,2               |
| <b>Degree of protection (IN) / (OUT)</b>                             |                                      | (IP)  | IPX4/IPX4         |
| <b>Class of electric protection (IN) / (OUT)</b>                     |                                      | Class I / Class II                                      | I/I               |
| <b>Max. input consumption</b>  |                                      | W   | 2150              |
| <b>Max. current</b>  |                                      | A   | 10                |
| <b>Compressor</b>  | Model                                |   | KSK103D33UEZ3(YJ) |
|  | Type                                 |   | Rotary            |
|  | Brand                                |   | GMCC              |
| <b>Indoor</b>  | <b>Fan motor</b>                     | Model   | ZKFP-13-8-4       |
|  |                                      | Power input   | W                 |
|  |                                      | Capacity  | uF                |
|  |                                      | Indoor Fan Speed RPM                                    | 700/900/1050      |
|  | Indoor fan                           | Dia. / Length   | mm                |
|  | Indoor Air Circulation               |   | m³/h              |
|  | Indoor Noise Level dB                |   | dB(A)             |
|  | Net Dimension (L×W×H)                |   | mm                |
|  | Packing Dimension (L×W×H)            |   | mm                |
|  | Net Weight/Gross Weight              |   | Kg                |
| <b>Outdoor</b>   | <b>Fan motor</b>                     | Model   | ZKFN-20-8-1       |
|  |                                      | Power input   | W                 |
|  |                                      | Capacity  | uF                |
|  |                                      | Outdoor Fan Speed RPM                                   | r/min             |
|  | Outdoor fan                          | Length  | mm                |
|  | Outdoor Noise Level dB               |   | dB(A)             |
|  | Net Dimension (L×W×H)                |   | mm                |
|  | Packing Dimension (L×W×H)            |   | mm                |
|  | Net Weight/Gross Weight              |   | Kg                |
|  | Refrigerant type/weight              |   | g                 |
|  | Max. Discharge/Max. Suction pressure |   | Mpa               |
| <b>Refrigerant piping</b>  |                                      | Liquid side / Gas side                                  | mm                |
|  |                                      | Max. refrigerant pipe length / Max. difference in level | m                 |
|  |                                      |   | 25/10             |