



Features

High-density filter, Self-cleaning, Low ambient kit (function), 4 indoor fan speeds, 5 outdoor unit fan motor speeds, Special coating on the evaporator, Refrigerant leakage detection, Turbo operation, Emergency use (when the temperature sensor is abnormal), Sleep mode, 1W in standby mode, 2 connection methods, Automatic restart, Timer, H-shaped installation plate, Air vent position memory, Intelligent switch, Breeze.

Capacity			9000BTU
Rated volt and frequency			220-240V~/50HZ
Mode	V/Hz	Cooling	Heating
Rated capacity		9000(3100~11600)	10000(2800~11500)
Power input	W	800(100~1240)	930(120~1200)
Current input	W	3.48(0.4~5.4)	4.05(0.5~5.5)
SEER-/ Energy Class	A	7,0/A++	/
SCOP/ Energy Class - average		/	4,1/A+
SCOP/ Energy Class - warmer		/	5,1/A+++
Operating range		15-50	-20-30
Energy consumption (per year, based on standard test results)	°C	188	/
Energy consumption (per year, based on standard test results) - average	kWh	/	957
Energy consumption (per year, based on standard test results) - warmer	kWh	/	823
Dehumidifying	Kg/h		1,7
Degree of protection (IN) / (OUT)	(IP)		IPX0/IPX4
Class of electric protection (IN) / (OUT)	Class I / Class II		I/I
Max. input consumption	W		2150
Max. current	A		10
Compressor	Model		KSK103D32UEZ31
	Type		Rotary
	Brand		GMCC
Indoor	Indoor Air Circulation	m³/h	435
	Indoor Noise Level dB	dB(A)	37/32/25/21.5
	Net Dimension	mm	715x194x285
	Packing Dimension	mm	780x270x365
	Net Weight/Gross Weight	Kg	6.7/8.8
Outdoor	Outdoor Noise Level dB	dB(A)	59
	Net Dimension	mm	720x270x495
	Packing Dimension	mm	835x300x540
	Net Weight/Gross Weight	Kg	21/22.8
	Refrigerant type		R32
	Refrigerant weight	Kg	0,47
	GWP		675
	tCO₂eq.		0,35
Max. Discharge/Max. Suction pressure	Mpa	4.3/1.7	
Refrigerant piping	Liquid side/ Gas side/Length	mm	Dg4/Dg8(1/4-3/8)
	Max. refrigerant pipe length/ Max. difference in level	m	25/10