



Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn OFF/ON, 4-Fan Speed, Five-speed outdoor fan motor, Honeycomb filter, Washable filter, Dual side Drainage, Remote control, Horizontal louver auto-swing, Hidden led display, Display ON/OFF, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, Top plate/cover, Anti-Cold Air

Capacity			18000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			Cooling Heating
Rated capacity		W	4990 5130
Power input		W	1554 1420
Current input		A	7,40 6,80
EER-COP/ Energy Class		W/W	3,21/ A 3,61/ A
Operating range		(°C)	15 - 43°C -7~24°C
Energy consumption (per year, based on standard test results)		kwh	1003
Dehumidifying		Kg/h	1,8
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	2130
Max. current		A	10
Compressor		Model	C-6RZ146H1DJ
		Type	Rotary
		Brand	RECHI
Indoor	Fan motor	Model	1170030067J
		Power input	W 25W output
		Capacity	uF /
		Indoor Fan Speed RPM	r/min ≤1350
	Indoor fan	Dia. / Length	mm φ98×702
	Indoor Air Circulation	m ³ /h	800
	Indoor Noise Level dB	dB(A)	43/40/38/35/34
	Net Dimension (L×W×H)	mm	910×294×206
Packing Dimension (L×W×H)	mm	979×372×277	
Net Weight/Gross Weight	Kg	10,5/12,5	
Outdoor	Fan motor	Model	1170040059
		Power input	W 40W output
		Capacity	uF /
		Outdoor Fan Speed RPM	r/min ≤1000
	Outdoor fan	Length	mm φ439×154
	Outdoor Noise Level dB	dB(A)	55
	Net Dimension (L×W×H)	mm	817×300×553
	Packing Dimension (L×W×H)	mm	858×321×585
	Net Weight/Gross Weight	Kg	32,5/35
	Refrigerant type/weight	Kg	R410A/0.930
Refrigerant piping	Liquid side / Gas side	mm	6.35/12
	Max. refrigerant pipe length /	m	15/5
	Max. difference in level		