JESLA



Turbo mode

When the air conditioner goes into Turbo mode, it will maximize its cooling or heating capacity, making the room cooler or warmer rapidly.



I FEEL

The remote control can keep track of the temperature at its current location and send the signal to the air conditioner, so it can optimize the room temperature for your maximum comfort.



Anti-fungus

The air conditioner will start the Anti-fungus feature after exiting cooling and dehumidifying mode. It helps prevent fungi and bacteria from spreading in order to maintain a healthy environment.



Horizontal swing

You can use the horizontal swing feature to adjust the airflow direction, if you prefer the air from the AC to blow sideways.



Intelligent defrosting

If the condenser freezes while in heating mode during the times of low outside temperature, the AC will start intelligent defrosting mode.





R32 Inverter Split Type Model TT68EX81-2432IAW



I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five-speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low-Temperature Heating/Cooling, Honeycomb filter, Washable filter, Dual side Drainage, Stability Protection, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, RC holder, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Horizontal swing, Wi-Fi, Additional Health filter

Capacity				24000BTU		
Rated volt and frequency			V/Hz	220-240V	220-240V~/50Hz/1P	
Mode			Cooling	Heating		
Rated capacity			W	6810(1830~7800)	6870(1850~7900)	
Power input			W	2257(410~2824)	2063(420~3005)	
Current input			Α	10.7(2.3~12.3)	9.9(2.3~13.5)	
SEER / Energy Class				6,1/A++	/	
SCOP / Energy Class - average				/	4.0/A+	
SCOP / Energy Class - warmer				/	5,1/A+++	
Operating range (°C)			°C	15-53	-20-30	
Energy consumption (per year, based on standard test results)			kWh	390	/	
Energy consumption (per year, based on standard test results) - average			kWh	/	1680	
Energy consumption (per year, based on standard test results) - warmer		kWh	/	1592		
Dehumidifying		Kg/h	1,8			
Degree of protection (IN) / (OUT)			(IP)	IPX0/IPX4		
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I			
Max. input consumption			W	3005		
Max. current		A	13,5			
	Model Compressor Type					
Co				Rotary		
		Brand		SANYO		
	Indoor Air Circulation		m³/h	980		
ō	Indoor Noise Level dB		dB(A)	54/51/48/44/40		
ndoor	Net Dimension		mm	1010×315×220		
-	Packing Dimension		mm	1096×390×297		
	Net Weight / Gro	ss Weight	Kg	13/16		
	Outdoor Noise Le	evel dB	dB(A)	57		
	Net Dimension		mm	920×699×380		
	Packing Dimension		mm	960×732×400		
90	Net Weight / Gross Weight		Kg	40/43		
Outdoor	Refrigerant Type			R32		
δ	Refrigerant Weight		Kg	1,14		
	GWP			675		
	tCO ₂ eq.			0,77		
	Max. Discharge / Max. Suction pressure		Мра	3,7/1,2		
Liquid side / Gas side / Length Refrigerant piping Max. refrigerant pipe length / Max. difference in level		mm	Dg4/Dg8 (1/4-1/2)			
			m	25/10		