



Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn OFF/ON, 4-Fan Speed, Five-speed outdoor fan motor, Honeycomb filter, Washable filter, Dual side Drainage, Remote control, Horizontal louver auto-swing, Hidden led display, Display ON/OFF, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, Top plate/cover, Anti-Cold Air

Capacity			24000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	6450 6740	
Power input		W	2005 1865	
Current input		A	9,5 8,8	
EER-COP/ Energy Class		W/W	3,21/ A 3,61/ A	
Operating range		(°C)	14 - 53°C -7~24°C	
Energy consumption (per year, based on standard test results)		kwh	1003	
Dehumidifying		Kg/h	2,2	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	2830	
Max. current		A	13,1	
Compressor		Model	ATN150D42UFZ	
		Type	DC	
		Brand	HIGHLY	
Indoor	Fan motor	Model	1170030101B	
		Power input	W	45W output
		Capacity	uF	3
		Indoor Fan Speed RPM	r/min	≤1280
	Indoor fan	Dia. / Length	mm	φ111.5X1010
	Indoor Air Circulation		m ³ /h	850
	Indoor Noise Level dB		dB(A)	43/41/38/37/35
	Net Dimension (LxWxH)		mm	910×294×206
	Packing Dimension (LxWxH)		mm	979×372×277
Net Weight/Gross Weight		Kg	10,5/12,5	
Outdoor	Fan motor	Model	1170040100	
		Power input	W	70W output
		Capacity	uF	/
		Outdoor Fan Speed RPM	r/min	≤1000
	Outdoor fan	Length	mm	φ536×153
	Outdoor Noise Level dB		dB(A)	55
	Net Dimension (LxWxH)		mm	886×357×605
	Packing Dimension (LxWxH)		mm	930×380×635
	Net Weight/Gross Weight		Kg	43/46
	Refrigerant type/weight		Kg	R410A/1.300
Max. Discharge/Max. Suction pressure		Mpa	4.5/1.9	
Refrigerant piping	Liquid side / Gas side		mm	6.35/15.88
	Max. refrigerant pipe length / Max. difference in level		m	15/5