



Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low Temperature Heating/Cooling, Honeycomb filter, Washable filter, High density filter, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Horizontal louver auto swing, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, Horizontal swing, RC holder, Additional Health filter, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Wi Fi, Additional Health filter, Tray heater

Capacity			18000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			Cooling Heating
Rated capacity		W	5100(1250-5900) 5130(1250-6080)
Power input		W	1574 1382
Current input		A	8,20 7,20
SEER-SCOP/ Energy Class		W/W	6,1 A++ 4 A+
Operating range		(°C)	0 - 53°C -20°C - 30°C
Energy consumption (per year, based on standard test results)		kwh	293 1330
Dehumidifying		Kg/h	1,8
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	2550
Max. current		A	13
Compressor	Model		KSN98D32UEZ
	Type		Rotary
	Brand		SANYO
Indoor	Fan motor	Model	1170030067G
		Power input	W 20W output
		Capacity	uF 2
		Indoor Fan Speed RPM	r/min ≤1320
	Indoor fan	Dia. / Length	mm φ92×578
		Indoor Air Circulation	m³/h 820
	Indoor Noise Level dB		dB(A) 50/47/43/36
	Net Dimension (L×W×H)		mm 920×306×195
	Packing Dimension (L×W×H)		mm 990×380×265
	Net Weight/Gross Weight		Kg 11/13
Outdoor	Fan motor	Model	1170040162AB
		Power input	W 33W output
		Capacity	uF /
		Outdoor Fan Speed RPM	r/min ≤1000
	Outdoor fan	Length	mm φ384×134
	Outdoor Noise Level dB		dB(A) 55
	Net Dimension (L×W×H)		mm 853×602×349
	Packing Dimension (L×W×H)		mm 890×628×385
	Net Weight/Gross Weight		Kg 35/38
	Refrigerant type/weight		g R32/1.00kg
Max. Discharge/Max. Suction pressure		Mpa 3.7/1.2	
Refrigerant piping	Liquid side / Gas side	mm	6.35/9.52
	Max. refrigerant pipe length / Max. difference in level	m	25/10