



Package contents

- 1 x Indoor Units 9000BTU
- 1 x Indoor Units 12000BTU
- 1 x Outdoor Unit 18000 BTU
- Remote Control
- User Manual

| Wall mounted ODU | | | TGS-D18V912W |
|-------------------------|--|--------------------------|------------------------|
| Power supply | | V/ N/ Hz | 220-240/1/50 |
| Capacity | Cooling | Capacity | Btu/h 7000-18000 |
| | | Input | W 1650 |
| | | Rated current | A 7,3 |
| | | EER | W/W 3,21 |
| | | SEER | 6,1 |
| | Heating | Capacity | Btu/h 8000-20000 |
| | | Input | W 1730 |
| | | Rated current | A 7,97 |
| | | COP | W/W 3,41 |
| | | SCOP | 4 |
| Max | Current | A 13,2 | |
| | Input | W 2500 | |
| Physical data | Outdoor air flow (High speed) | | m ³ /h 2300 |
| | Sound pressure noise level | | dB(A) 55 |
| | Sound power noise level | | dB(A) 65 |
| | Net dimension (WxHxD) | | mm 880x555x345 |
| | Packing dimension (WxHxD) | | mm 920x600x380 |
| | Net/Gross weight | | kg 33,2/36 |
| | Refrigerant type and quantity | | g R32/1350 |
| Piping data | Liquid side/Gas side | | mm 2x(6.35/9.52) |
| | Max. pipe length (total) | | m 30 |
| | Max. height difference between indoor unit and outdoor unit (ODU below) | | m 10 |
| | Ambient temperature Cooling | | °C -15~52 |
| | Heating | | °C -15~34 |
| Application area | | m ² 2x(12~18) | |

| Wall mounted IDU | | | TGS-D18V912W | TGS-D18V912W | |
|-----------------------------------|-------------------------|--------------------------------------|----------------------|--------------------|----------|
| Power supply | | V/ N/ Hz | 220-240/1/50 | 220-240/1/50 | |
| Capacity | Cooling | Capacity | Btu/h 9000 | 12000 | |
| | | Input | W 35 | 45 | |
| | | Rated current | A 0,3 | 0,4 | |
| | | Heating | Capacity | Btu/h 10000 | 13000 |
| | | | Input | W 35 | 45 |
| | Rated current | | A 0,3 | 0,4 | |
| | Physical data | Indoor air flow | | m ³ 450 | 550 |
| | | Indoor noise level (Hi/Mi/Lo) | | dB(A) 33/28/24 | 36/30/25 |
| | | Sound power noise level | | dB(A) 50 | 50 |
| Net dimensions (WxHxD) | | mm 715x295x198 | 864x300x200 | | |
| Packing dimensions (WxHxD) | | mm 785x370x285 | 950x380x290 | | |
| Net/Gross weight | | kg 8,5/10,5 | 9,5/11,5 | | |
| Piping data | Liquid/Gas | | mm 6,35/9,52 | 6,35/9,52 | |
| | Drainage pipe | | mm DN17 | DN17 | |
| | Application area | | m ² 12-18 | 16-23 | |