



Package contents

- 3 x Indoor Units 9000BTU
- 1 x Indoor Units 12000BTU
- 1 x Outdoor Unit 36000 BTU
- Remote Control
- User Manual

Wall mounted ODU			TGS-D36V99912W		
Power supply		V/ N/ Hz	220-240/1/50		
Capacity	Cooling	Capacity	Btu/h	7000-27000	
		Input	W	2472	
		Rated current	A	10,9	
		EER	W/W	3,2	
		SEER		6,2	
	Heating	Capacity	Btu/h	8000-30000	
		Input	W	2600	
		Rated current	A	10,8	
		COP	W/W	3,38	
	Max	SCOP		4	
Current		A	17,2		
Physical data	Input	W	3500		
	Outdoor air flow (High speed)	m ³ /h	3300		
	Sound pressure noise level	dB(A)	56		
	Sound power noise level	dB(A)	66		
	Net dimension (WxHxD)	mm	938x702x382		
	Packing dimension (WxHxD)	mm	975x770x435		
	Net/Gross weight	kg	51.3/54.5		
	Refrigerant type and quantity	g	R32/1800		
Piping data	Liquid side/Gas side	mm	3x(6.35/9.52)		
	Max. pipe length (total)	m	45		
	Max. height difference between indoor unit and outdoor unit (ODU below)	m	10		
	Ambient temperature Cooling	°C	-15~52		
	Heating	°C	-15~34		
Application area	m ²	3x(12~18)			

Wall mounted IDU			TGS-D36V99912W		TGS-D36V99912W		
Power supply			V/ N/ Hz	220-240/1/50	220-240/1/50		
Capacity	Cooling	Capacity	Btu/h	9000	12000		
		Input	W	35	45		
		Rated current	A	0,3	0,4		
	Heating	Capacity	Btu/h	10000	13000		
		Input	W	35	45		
		Rated current	A	0,3	0,4		
	Physical data	Indoor air flow		m ³	450	550	
		Indoor noise level (Hi/Mi/Lo)		dB(A)	33/28/24	36/30/25	
		Sound power noise level		dB(A)	50	50	
Net dimensions (WxHxD)		mm	715x295x198	864x300x200			
Packing dimensions (WxHxD)		mm	785x370x285	950x380x290			
Net/Gross weight		kg	8,5/10,5	9,5/11,5			
Piping data	Liquid/Gas		mm	6,35/9,52	6,35/9,52		
	Drainage pipe		mm	DN17	DN17		
	Application area		m ²	12-18	16-23		