




I FEEL

The remote control can keep track of the temperature at its current location and send the signal to the air conditioner, so it can optimize the room temperature for your maximum comfort.



HORIZONTAL SWING

You can use the horizontal swing feature to adjust the airflow direction, if you prefer the air from the AC to blow sideways.



3D AIRFLOW

Depending on the model, you can choose between different air dispersion positions available, such as blanket-style, shower-style, breeze etc.



RC HOLDER

Keep your remote control conveniently stored in its holder, so you always know where it is when you need it.



WI-FI

Wi-Fi feature means that Tesla air conditioner can also be controlled with mobile phones or other smart devices: an option that adds to your everyday convenience and comfort!



Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five-speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low-Temperature Heating/Cooling, Honeycomb filter, Washable filter, Dual side Drainage, Stability Protection, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, RC holder, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Mute mode, Remote with backlight, Special coating for evaporator

Capacity		9000BTU	
Rated volt and frequency		V/Hz 220-240V~/50Hz/1P	
Mode		Cooling	Heating
Rated capacity		W 2600(940~3300)	2610(940~3360)
Power input		W 825(240-1380)	767(240-1552)
Current input		A 4.0(1.2~8.0)	3.8(1.2~9.0)
SEER / Energy Class		6,1/A++	/
SCOP / Energy Class - average		/	4.0/A+
SCOP / Energy Class - warmer		/	5,1/A+++
Operating range (°C)		°C 15-53	-20-30
Energy consumption (per year, based on standard test results)		kWh 149	/
Energy consumption (per year, based on standard test results) - average		kWh /	700
Energy consumption (per year, based on standard test results) - warmer		kWh /	604
Dehumidifying		Kg/h 1.2	
Degree of protection (IN) / (OUT)		(IP) IPX0/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II I/I	
Max. input consumption		W 1552	
Max. current		A 9	
Compressor		Model	
		Type	Rotary
		Brand	RECHI
Indoor	Indoor Air Circulation	m³/h 550	
	Indoor Noise Level dB	dB(A) 50/47/43/35/32	
	Net Dimension	mm 777×250×201	
	Packing Dimension	mm 840×315×260	
	Net Weight / Gross Weight	Kg 7,5/10	
Outdoor	Outdoor Noise Level dB	dB(A) 50	
	Net Dimension	mm 712×276×459	
	Packing Dimension	mm 765×310×481	
	Net Weight / Gross Weight	Kg 22/24	
	Refrigerant Type	R32	
	Refrigerant Weight	Kg 0,49	
	GWP	675	
	tCO ₂ eq.	0,33	
Max. Discharge / Max. Suction pressure		Mpa 3,7/1,2	
Refrigerant piping		Liquid side / Gas side / Length	mm Dg4/Dg8(1/4-3/8)
		Max. refrigerant pipe length / Max. difference in level	m 25/10