

TESLA



R32 Inverter Split Type Model
TT34TP81-1232IAWT



Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low Temperature Heating/Cooling, Honeycomb filter, Washable filter, High density filter, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Horizontal louver auto swing, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, Horizontal swing, RC holder, Additional Health filter, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Wi Fi, Additional Health filter, Energy Efficiency, Tray Heater

Capacity		12000BTU	
Rated volt and frequency		V/Hz 220-240V~/50Hz/1P	
Mode		Cooling	Heating
Rated capacity	W	3500(1000~4000)	3620(1000~4300)
Power input	W	1162(290~1500)	1090(290~1730)
Current input	A	5.5(1.5~9.0)	5.1/A++(1.5~10.0)
SEER / Energy Class		6,5/A++	/
SCOP / Energy Class - average		/	4.0/A+
SCOP / Energy Class - warmer		/	5,1/A+++
Operating range (°C)		°C 15-53	-25-30
Energy consumption (per year, based on standard test results)		kWh 188	/
Energy consumption (per year, based on standard test results) - average		kWh /	840
Energy consumption (per year, based on standard test results) - warmer		kWh /	741
Dehumidifying		Kg/h 1,2	
Degree of protection (IN) / (OUT)		(IP) IPX0/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II I/I	
Max. input consumption		W 1730	
Max. current		A 10	
Compressor		Model	
		Type	Rotary
		Brand	RECHI
Indoor	Indoor Air Circulation	m ³ /h	560
	Indoor Noise Level dB	dB(A)	54/47/45/43/39/35/32
	Net Dimension	mm	790×275×192
	Packing Dimension	mm	795×549×305
	Net Weight / Gross Weight	Kg	8,5/10,5
Outdoor	Outdoor Noise Level dB	dB(A)	52
	Net Dimension	mm	795×549×305
	Packing Dimension	mm	835×340×585
	Net Weight / Gross Weight	Kg	25/28
	Refrigerant Type		R32
	Refrigerant Weight	Kg	0,7
	GWP		675
	tCO₂eq.		0,47
	Max. Discharge / Max. Suction pressure	Mpa	3,7/1,2
Refrigerant piping	Liquid side / Gas side / Length	mm	Dg4/Dg8 (1/4-3/8)
	Max. refrigerant pipe length / Max. difference in level	m	15/10