JESLA



Turbo mode

When the air conditioner goes into Turbo mode, it will maximize its cooling or heating capacity, making the room cooler or warmer rapidly.



I FEEL

The remote control can keep track of the temperature at its current location and send the signal to the air conditioner, so it can optimize the room temperature for your maximum comfort.



Anti-fungus

The air conditioner will start the Anti-fungus feature after exiting cooling and dehumidifying mode. It helps prevent fungi and bacteria from spreading in order to maintain a healthy environment.



Horizontal swing

You can use the horizontal swing feature to adjust the airflow direction, if you prefer the air from the AC to blow sideways.



Intelligent defrosting

If the condenser freezes while in heating mode during the times of low outside temperature, the AC will start intelligent defrosting mode.





R32 Inverter Split Type Model TT51TP21-1832IAW



JESLA

Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto m Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low Temperature Heating/Cooling, Honeycomb filter, Washable filter, High density filter, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Horizontal $louver auto swing, Hidden \ led \ display, Display \ ON/OFF, Comfortable \ Cooling, Strong \ Cooling \ at \ 60^{\circ}C, Rapid \ Cooling \ and \ Rapid \ Heating, Horizontal$ swing, RC holder, Additional Health filter, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Wi Fi, Additional Health filter

Capacity				18000BTU	
Rated volt and frequency		V/Hz	220-240V~/50Hz/1P		
Mode			Cooling	Heating	
Rated capacity			W	5100(1250-5900)	5130(1250-6080)
Power input			W	1574(330-2350)	1382(340-2550)
Current input			A	8.2(1.7~12.0)	7.2(1.7~13.0)
SEER / Energy Class				6,1/A++	/
SCOP / Energy Class - average				/	4.0/A+
SCOP / Energy Class - warmer				/	5,1/A+++
Operating range (°C)			°C	15-53	-20-30
Energy consumption (per year, based on standard test results)			kWh	293	/
Energy consumption (per year, based on standard test results) - average			kWh	/	1330
Energy consumption (per year, based on standard test results) - warmer		kWh	/	1373	
Dehumidifying		Kg/h	1,5		
Degree of protection (IN) / (OUT)		(IP)	IPX0/IPX4		
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I		
Max. input consumption			W	2550	
Max. current		A	13		
	Model Compressor Type				
C				Rotary	
		Brand		SANYO	
	Indoor Air Circulation		m³/h	820	
ō	Indoor Noise Level dB		dB(A)	54/50/47/43/36	
Indoor	Net Dimension		mm	920×306×195	
_	Packing Dimension	on	mm	990×380×265	
	Net Weight / Gross Weight		Kg	11/13	
	Outdoor Noise Level dB		dB(A)	55	
	Net Dimension		mm	853×602×349	
	Packing Dimension		mm	890×628×385	
20	Net Weight / Gross Weight		Kg	35/38	
Outdoor	Refrigerant Type			R32	
ŏ	Refrigerant Weight		g	1	
	GWP			675	
	tCO ₂ eq.			0,68	
	Max. Discharge / Max. Suction pressure		Мра	3,7/1,2	
Liquid side / Gas side / Length Refrigerant piping Max. refrigerant pipe length / Max. difference in level		mm	Dg4/Dg8 (1/4-3/8)		
			m	25/10	