



Power supply	220-240V/1Ph/50Hz		
Heating performances	A+7°C; W30/35°C		
	Heating capacity	kW	16,00
	COP (>4.5)		4,60
	A+2°C; W30/35°C		
	Heating capacity	kW	14,50
	COP (>3.5)		3,30
	A-7°C; W30/35°C		
	Heating capacity	kW	13,30
	COP (>2.7)		2,70
	A+7°C; W40/45°C		
	Heating capacity	kW	16,00
	COP (>3.6)		3,50
	A+7°C; W47/55°C		
	Heating capacity	kW	13,50
	COP (>2.9)		2,70
	A+2°C; W47/55°C		
	Heating capacity	kW	13,50
	COP		2,35
	A-7°C; W47/55°C		
	Heating capacity	kW	11,50
	COP		1,95
	A+7°C; W35°C (ErP-average)		
	Prated-NET		14,79
	SCOP-NET		4,78
ηs 30/35-NET	%	188%	
Efficiency class 30/35		A+++	
A+7°C; W55°C (ErP-average)			
Prated-NET		13,06	
SCOP-NET		3,36	
ηs 47/55-NET	%	131%	
Efficiency class 47/55		A++	
Cooling performances	A+35°C; W23/18°C		
	Cooling capacity	kW	14,50
	EER (>3.8)		3,80
	SEER		6,14
	ηs 23/18		243%
	A+35°C; W12/7°C		
	Cooling capacity	kW	14,00
	EER (>3.1)		2,65
	SEER		5,06
	ηs 12/7		199%

Physical data			
Sound levels	Standard unit		
	Sound power level [2]	dB(A)	70
	Sound pressure level [3]	dB(A)	58
Current	Max.	A	30+13.6
Dimensions	Length	mm	1302
	Width	mm	465
	Height	mm	1517
	Package	mm	1364*518*1690
Weight (1)	Standard unit	kg	167,7
	Package	kg	184,4
Compressors	Compressor type	DC Twin-rotary	
	Copressor qty	1	
Refrigerant	Type	R32	
	Charge [1]	kg	2,6
Condenser	Copper	Hydrophilic aluminum foil	
	Fin type	Hydrophilic aluminum foil	
Fans	Fan type	Axial type	
	Fan quantity		2
	Rated total air flow	m³/h	7300
	Rated speed	rpm	860
Evaporator	Type	Brazeed plate heat exchanger	
	Water volume	L	1,45
Hydraulic module		Circulator, relief valve, paddle flow switch, expansion tank	
	Circulator	Centrifugal pump (variable speed)	
	Expansion tank volume	L	5
	Auxiliary electrical heater	kW	3
	Max. water-side operating pressure with hydraulic module [4]	kPa	90
Water connections	Inlet diameter (MPT GAS)	inch	1,25
	Outlet diameter (MPT GAS)	inch	1,25
Ambient temperature range	Cooling	°C	-5-50
	Heating	°C	-25-43
	DHW	°C	-25-43
Water outlet temperature range	Cooling	°C	5-25
	Heating	°C	25-62
	DHW	°C	40-62

1. Values are guidelines only. Refer to the unit nameplate.
2. Declared dualnumber noise emission values in accordance with ISO 4871 (with an associated uncertainty of +/-2dB(A)). Measured in accordance with ISO 9614-1.
3. Declared dualnumber noise emission values in accordance with EN12102-1 (with an associated uncertainty of +/-2dB(A)). For information, calculated from the sound power level Lw(A).
4. Min. water-side operating pressure with variable speed hydraulic module is 40 kPa.