



Package contents

- 2 x Indoor Units 9000BTU
- 1 x Outdoor Unit 14000 BTU
- Remote Control
- User Manual

Wall mounted ODU			TGSJ2-16DA1
Power supply		V/ N/ Hz	220-240/1/50
Capacity	Cooling	Capacity	Btu/h 7000~14000
		Input	W 1280
		Rated current	A 5,56
		EER	W/W 3,2
		SEER	6,2
	Heating	Capacity	Btu/h 8000~16000
		Input	W 1350
		Rated current	A 6,4
		COP	W/W 3,48
	Max	SCOP	4
Current		A 11,4	
Physical data	Input	W 2300	
	Outdoor air flow (High speed)	m ³ /h 2300	
	Sound pressure noise level	dB(A) 55	
	Sound power noise level	dB(A) 65	
	Net dimension (W×H×D)	mm 880×555×345	
	Packing dimension (W×H×D)	mm 920×600×380	
	Net/Gross weight	kg 32.4/35.1	
	Refrigerant type and quantity	g R32/1100	
Piping data	Liquid side/Gas side	mm 2×(6.35/9.52)	
	Max. pipe length (total)	m 30	
	Max. height difference between indoor unit and outdoor unit (ODU below)	m 10	
	Ambient temperature Cooling	°C -15~52	
	Heating	°C -15~34	
Application area	m ² 2*(10~15)		

Wall mounted IDU			TGZU-D09P4A1
Power supply		V/ N/ Hz	220-240/1/50
Capacity	Cooling	Capacity	Btu/h 9000
		Input	W 35
		Rated current	A 0,3
	Heating	Capacity	Btu/h 10000
		Input	W 35
		Rated current	A 0,3
Physical data	Indoor air flow	m ³ 450	
	Indoor noise level (Hi/Mi/Lo)	dB(A) 33/28/24	
	Sound power noise level	dB(A) 50	
	Net dimensions (W×H×D)	mm 715x295x198	
	Packing dimensions (W×H×D)	mm 785x370x285	
	Net/Gross weight	kg 8,5/10,5	
Piping data	Liquid/Gas	mm 6,35/9,52	
	Drainage pipe	mm DN17	
	Application area	m ² 12-18	