



### Package contents

- 2 x Indoor Units 12000BTU
- 1 x Outdoor Unit 21000 BTU
- Remote Control
- User Manual

Wall mounted ODU			TGSJ3-D21C1
<b>Power supply</b>		V/ N/ Hz	220-240/1/50
<b>Capacity</b>	<b>Cooling</b>	<b>Capacity</b>	Btu/h 7000-21000
		<b>Input</b>	W 1930
		<b>Rated current</b>	A 8,4
		<b>EER</b>	W/W 3,21
		<b>SEER</b>	6,3
	<b>Heating</b>	<b>Capacity</b>	Btu/h 8000-24000
		<b>Input</b>	W 2150
		<b>Rated current</b>	A 10,8
		<b>COP</b>	W/W 3,26
	<b>Max</b>	<b>SCOP</b>	4
<b>Current</b>		A 14,2	
<b>Physical data</b>	<b>Input</b>	W 2880	
	<b>Outdoor air flow (High speed)</b>	m <sup>3</sup> /h 3300	
	<b>Sound pressure noise level</b>	dB(A) 56	
	<b>Sound power noise level</b>	dB(A) 66	
	<b>Net dimension (WxHxD)</b>	mm 938x702x382	
	<b>Packing dimension (WxHxD)</b>	mm 975x770x435	
	<b>Net/Gross weight</b>	kg 46.3/49.5	
	<b>Refrigerant type and quantity</b>	g R32/1600	
<b>Piping data</b>	<b>Liquid side/Gas side</b>	mm 3x(6.35/9.52)	
	<b>Max. pipe length (total)</b>	m 45	
	<b>Max. height difference between indoor unit and outdoor unit (ODU below)</b>	m 10	
	<b>Ambient temperature Cooling</b>	°C -15~52	
	<b>Heating</b>	°C -15~34	
<b>Application area</b>	m <sup>2</sup> 3*(10~15)		

Wall mounted IDU			TGZUJ-V12P4
<b>Power supply</b>		V/ N/ Hz	220-240/1/50
<b>Capacity</b>	<b>Cooling</b>	<b>Capacity</b>	Btu/h 12000
		<b>Input</b>	W 45
		<b>Rated current</b>	A 0,4
	<b>Heating</b>	<b>Capacity</b>	Btu/h 13000
		<b>Input</b>	W 45
		<b>Rated current</b>	A 0,4
<b>Physical data</b>	<b>Indoor air flow</b>	m <sup>3</sup>	550
	<b>Indoor noise level (Hi/Mi/Lo)</b>	dB(A)	36/30/25
	<b>Sound power noise level</b>	dB(A)	50
	<b>Net dimensions (WxHxD)</b>	mm	864x300x200
	<b>Packing dimensions (WxHxD)</b>	mm	950x380x290
	<b>Net/Gross weight</b>	kg	9,5/11,5
<b>Piping data</b>	<b>Liquid/Gas</b>	mm	6,35/9,52
	<b>Drainage pipe</b>	mm	DN17
	<b>Application area</b>	m <sup>2</sup>	16-23