



Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low Temperature Heating/Cooling, Honeycomb filter, Washable filter, High density filter, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Horizontal louver auto swing, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, Horizontal swing, RC holder, Additional Health filter, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Wi Fi, Additional Health filter

| | | | |
|--|--|--------------------|---|
| Capacity | | | 18000BTU |
| Rated volt and frequency | | V/Hz | 220-240V~/50HZ |
| Mode | | | Cooling Heating |
| Rated capacity | W | 5400(1300-5900) | 5600(1300-6000) |
| Power input | W | 1700(290-2100) | 1600(250-1800) |
| Current input | A | 7.5(2.2-9,3) | 7.0(2,0-8) |
| SEER / Energy Class | | | 7,3/A++ / |
| SCOP / Energy Class - average | | | / 4,3/A+ |
| SCOP / Energy Class - warmer | | | / 5,1/A+++ |
| Operating range (°C) | | °C | 16-49 -25-30 |
| Energy consumption (per year, based on standard test results) | | kWh | 258 / |
| Energy consumption (per year, based on standard test results) - average | | kWh | / 1490 |
| Energy consumption (per year, based on standard test results) - warmer | | kWh | / 1359 |
| Dehumidifying | | Kg/h | 2,5 |
| Degree of protection (IN) / (OUT) | | (IP) | IPX0/IPX4 |
| Class of electric protection (IN) / (OUT) | | Class I / Class II | I/I |
| Max. input consumption | | W | 2400 |
| Max. current | | A | 12 |
| Compressor | Model | | KSN140D53UFZM3 |
| | Type | | Rotary |
| | Brand | | GMCC |
| Indoor | Indoor Air Circulation | m ³ /h | 950 |
| | Indoor Noise Level dB | dB(A) | 40/46/52/54/58 |
| | Net Dimension | mm | 960×315×221 |
| | Packing Dimension | mm | 1020×375×305 |
| | Net Weight / Gross Weight | Kg | 11,5/13,5 |
| Outdoor | Outdoor Noise Level dB | dB(A) | 62 |
| | Net Dimension | mm | 785×555×300 |
| | Packing Dimension | mm | 903×615×382 |
| | Net Weight / Gross Weight | Kg | 28/32 |
| | Refrigerant Type | | R32 |
| | Refrigerant Weight | Kg | 1,03 |
| | GWP | | 675 |
| | tCO₂eq. | | 0,70 |
| | Max. Discharge / Max. Suction pressure | Mpa | 4.3/2.5 |
| Refrigerant piping | Liquid side / Gas side / Length | mm | Dg4/Dg10(1/4-1/2) |
| | Max. refrigerant pipe length / Max. difference in level | m | 30/20 |