



Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low Temperature Heating/Cooling, Honeycomb filter, Washable filter, High density filter, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Horizontal louver auto swing, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, Horizontal swing, RC holder, Additional Health filter, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Wi Fi, Additional Health filter

Capacity		24000BTU	
Rated volt and frequency		V/Hz 220-240V~/50HZ	
Mode		Cooling	Heating
Rated capacity	W	7300(1800-7400)	7300(1800-8000)
Power input	W	2200(230-2760)	2200(230-2530)
Current input	A	7.3(1,8-7,4)	7.3(1,8-8,0)
SEER / Energy Class		6,53/A++	/
SCOP / Energy Class - average		/	4,09/A+
SCOP / Energy Class - warmer		/	5,27/A+++
Operating range (°C)		°C 16-49	-25-30
Energy consumption (per year, based on standard test results)		kWh 359	/
Energy consumption (per year, based on standard test results) - average		kWh /	1950
Energy consumption (per year, based on standard test results) - warmer		kWh /	1859
Dehumidifying		Kg/h 3,1	
Degree of protection (IN) / (OUT)		(IP) IPX0/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II I/I	
Max. input consumption		W 3400	
Max. current		A 16	
Compressor		Model	C-6RZ146H3DEF
		Type	Rotary
		Brand	SANYO
Indoor	Indoor Air Circulation	m ³ /h	1300
	Indoor Noise Level dB	dB(A)	41/47/53/56/63
	Net Dimension	mm	1089×328×227
	Packing Dimension	mm	1155×397×312
	Net Weight / Gross Weight	Kg	12,5/15,5
Outdoor	Outdoor Noise Level dB	dB(A)	66
	Net Dimension	mm	900×700×350
	Packing Dimension	mm	1015×762×425
	Net Weight / Gross Weight	Kg	39/44
	Refrigerant Type		R32
	Refrigerant Weight	Kg	1,3
	GWP		675
	tCO₂eq.		0,88
	Max. Discharge / Max. Suction pressure	Mpa	4.3/2.5
Refrigerant piping	Liquid side / Gas side / Length	mm	Dg4/Dg13(1/4-5/8)
	Max. refrigerant pipe length / Max. difference in level	m	30/20