



Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn OFF/ON, 4-Fan Speed, Five-speed outdoor fan motor, Honeycomb filter, Washable filter, Dual side Drainage, Remote control, Horizontal louver auto-swing, Hidden led display, Display ON/OFF, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, Top plate/cover, Anti-Cold Air

Capacity			24000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	4990 5130	
Power input		W	2005 1865	
Current input		A	9,50 8,80	
EER-COP/ Energy Class		W/W	3,21/ A 3,61/ A	
Operating range		(°C)	15 - 43°C -7°C - 24°C	
Energy consumption (per year, based on standard test results)		kwh	1003	
Dehumidifying		Kg/h	2,2	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	2700	
Max. current		A	14,8	
Compressor		Model	GSL236CV-C8DU4	
		Type	Rotary	
		Brand	HIGHLY	
Indoor	Fan motor	Model	22001-000273	
		Power input	W	14Woutput
		Capacity	uF	2
		Indoor Fan Speed RPM	r/min	≤1300
	Indoor fan	Dia. / Length	mm	φ92×578
	Indoor Air Circulation		m ³ /h	800
	Indoor Noise Level dB		dB(A)	43/41/38/37/35
	Net Dimension (L×W×H)		mm	910×294×206
	Packing Dimension (L×W×H)		mm	979×372×277
Net Weight/Gross Weight		Kg	10/13	
Outdoor	Fan motor	Model	22001-000007	
		Power input	W	25Woutput
		Capacity	uF	2
		Outdoor Fan Speed RPM	r/min	≤895
	Outdoor fan	Length	mm	φ320×119
	Outdoor Noise Level dB		dB(A)	48
	Net Dimension (L×W×H)		mm	853×349×602
	Packing Dimension (L×W×H)		mm	890×385×628
	Net Weight/Gross Weight		Kg	31/33,5
	Refrigerant type/weight		Kg	R32/0.880
Refrigerant piping	Liquid side / Gas side	mm	6,35/12,7	
	Max. refrigerant pipe length / Max. difference in level	m	15/5	