



## Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low Temperature Heating/Cooling, Honeycomb filter, Washable filter, High density filter, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Horizontal louver auto swing, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, Horizontal swing, RC holder, Additional Health filter, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Wi Fi

<b>Capacity</b>			18000BTU
<b>Rated volt and frequency</b>		V/Hz	220-240V~/50HZ
<b>Mode</b>			<b>Cooling</b> <b>Heating</b>
<b>Rated capacity</b>	<b>W</b>	5400(1300-5900)	5800(1300-6100)
<b>Power input</b>	<b>W</b>	1.43(0.29-1.95)	1.33(0.25-1.8)
<b>Current input</b>	<b>A</b>	6.4(2.2-6.8)	6.1(2.0-8.0)
<b>SEER / Energy Class</b>			8,7/A+++                      /
<b>SCOP / Energy Class - average</b>			/                      4,6/A++
<b>SCOP / Energy Class - warmer</b>			/                      5,5/A+++
<b>Operating range (°C)</b>		°C	16-49                      -55
<b>Energy consumption (per year, based on standard test results)</b>		kWh	215                      /
<b>Energy consumption (per year, based on standard test results) - average</b>		kWh	/                      1339
<b>Energy consumption (per year, based on standard test results) - warmer</b>		kWh	/                      1303
<b>Dehumidifying</b>		Kg/h	2.5
<b>Degree of protection (IN) / (OUT)</b>		(IP)	IPX0/IPX4
<b>Class of electric protection (IN) / (OUT)</b>		Class I / Class II	I/I
<b>Max. input consumption</b>		<b>W</b>	2400
<b>Max. current</b>		<b>A</b>	12
<b>Compressor</b>		<b>Model</b>	C-1RZ140H3DDF
		<b>Type</b>	Rotary
		<b>Brand</b>	SANYO
<b>Indoor</b>	<b>Indoor Air Circulation</b>	m <sup>3</sup> /h	1060
	<b>Indoor Noise Level dB</b>	dB(A)	56
	<b>Net Dimension</b>	mm	1140×332×230
	<b>Packing Dimension</b>	mm	1210×400×327
	<b>Net Weight / Gross Weight</b>	Kg	13.5/17
<b>Outdoor</b>	<b>Outdoor Noise Level dB</b>	dB(A)	63
	<b>Net Dimension</b>	mm	785×548×281
	<b>Packing Dimension</b>	mm	903×615×382
	<b>Net Weight / Gross Weight</b>	Kg	28.5/32
	<b>Refrigerant Type</b>		R32
	<b>Refrigerant Weight</b>	Kg	1,03
	<b>GWP</b>		675
	<b>tCO<sub>2</sub>eq.</b>		0,7
<b>Max. Discharge / Max. Suction pressure</b>		<b>Mpa</b>	4.3/2.5
<b>Refrigerant piping</b>		<b>Liquid side / Gas side / Length</b>	mm
		<b>Max. refrigerant pipe length / Max. difference in level</b>	m
			Dg4/Dg8 (1/4-3/8)
			25/15