



Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn OFF/ON, 4-Fan Speed, Five-speed outdoor fan motor, Honeycomb filter, Washable filter, Dual side Drainage, Remote control, Horizontal louver auto-swing, Hidden led display, Display ON/OFF, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, Top plate/cover, Anti-Cold Air

Capacity			9000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	2490 2650	
Power input		W	775 734	
Current input		A	3,70 3,50	
EER-COP/ Energy Class		W/W	3,21/ A 3,61/ A	
Operating range		(°C)	15 - 43°C -7°C - 24°C	
Energy consumption (per year, based on standard test results)		kwh	388	
Dehumidifying		Kg/h	1,0	
Degree of protection (IN) / (OUT)		(IP)	IPX4/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	1400	
Max. current		A	7,6	
Compressor		Model	KSM99V01UDZE	
		Type	Rotary	
		Brand	GMCC	
Indoor	Fan motor	Model	22001-000273	
		Power input	W	14Woutput
		Capacity	uF	2
		Indoor Fan Speed RPM	r/min	≤1300
	Indoor fan	Dia. / Length	mm	φ92×578
	Indoor Air Circulation	m ³ /h		450
	Indoor Noise Level dB	dB(A)		35/33/29/27/25
	Net Dimension (L×W×H)	mm		698×255×190
	Packing Dimension (L×W×H)	mm		764×325×257
Net Weight/Gross Weight	Kg		6,5/8,5	
Outdoor	Fan motor	Model	22001-000007	
		Power input	W	25Woutput
		Capacity	uF	2
		Outdoor Fan Speed RPM	r/min	≤895
	Outdoor fan	Length	mm	φ320×119
	Outdoor Noise Level dB	dB(A)		48
	Net Dimension (L×W×H)	mm		712×276×459
	Packing Dimension (L×W×H)	mm		765×310×481
	Net Weight/Gross Weight	Kg		23/25
Refrigerant type/weight	Kg		R32/0.430	
Max. Discharge/Max. Suction pressure	Mpa		4.5/1.9	
Refrigerant piping	Liquid side / Gas side	mm	6,35/9,52	
	Max. refrigerant pipe length / Max. difference in level	m	15/5	