



## Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low Temperature Heating/Cooling, Honeycomb filter, Washable filter, High density filter, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Horizontal louver auto swing, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, Horizontal swing, RC holder, Additional Health filter, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Wi Fi, Additional Health filter, Tray Heater

<b>Capacity</b>			18000BTU
<b>Rated volt and frequency</b>		V/Hz	220-240V~/50HZ
<b>Mode</b>			<b>Cooling</b> <b>Heating</b>
<b>Rated capacity</b>		W	5300(1300-5900)                      5600(1300-6100)
<b>Power input</b>		W	1.430(290-1.950)                      1.330(250-1.800)
<b>Current input</b>		A	6.4(2.2-6.8)                      6.1(2.0-8.0)
<b>SEER / Energy Class</b>			8,5/A+++                      /
<b>SCOP / Energy Class - average</b>			/                      4,6/A++
<b>SCOP / Energy Class - warmer</b>			/                      5,8/A+++
<b>Operating range (°C)</b>		°C	15-53                      -25-32
<b>Energy consumption (per year, based on standard test results)</b>		kWh	218                      /
<b>Energy consumption (per year, based on standard test results) - average</b>		kWh	/                      1340
<b>Energy consumption (per year, based on standard test results) - warmer</b>		kWh	/                      1279
<b>Dehumidifying</b>		Kg/h	2.500
<b>Degree of protection (IN) / (OUT)</b>		(IP)	IPX0/IPX4
<b>Class of electric protection (IN) / (OUT)</b>		Class I / Class II	I/I
<b>Max. input consumption</b>		W	2400
<b>Max. current</b>		A	12
<b>Compressor</b>		Model	C-1RZ140H3DDF
		Type	Rotary
		Brand	SANYO
<b>Indoor</b>	Indoor Air Circulation	m <sup>3</sup> /h	1000
	Indoor Noise Level dB	dB(A)	56
	Net Dimension	mm	1089×328×227
	Packing Dimension	mm	1155×397×312
	Net Weight / Gross Weight	Kg	13,5
<b>Outdoor</b>	Outdoor Noise Level dB	dB(A)	56
	Net Dimension	mm	785×555×300
	Packing Dimension	mm	903×615×382
	Net Weight / Gross Weight	Kg	28,5
	Refrigerant Type		R32
	Refrigerant Weight	Kg	1,03
	GWP		675
	tCO <sub>2</sub> eq.		0,70
	Max. Discharge / Max. Suction pressure	Mpa	4.3/2.5
	<b>Refrigerant piping</b>	Liquid side / Gas side / Length	mm
Max. refrigerant pipe length / Max. difference in level		m	25/15