



Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low Temperature Heating/Cooling, Honeycomb filter, Washable filter, High density filter, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Horizontal louver auto swing, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, Horizontal swing, RC holder, Additional Health filter, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Wi Fi, Additional Health filter, Tray Heater

Capacity			18000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			Cooling Heating
Rated capacity		W	5300(1300-5900) 5600(1300-6100)
Power input		W	1.430(290-1.950) 1.330(250-1.800)
Current input		A	6.4(2.2-6.8) 6.1(2.0-8.0)
SEER / Energy Class			8,5/A+++ /
SCOP / Energy Class - average			/ 4,6/A++
SCOP / Energy Class - warmer			/ 5,8/A+++
Operating range (°C)		°C	15-53 -25-32
Energy consumption (per year, based on standard test results)		kWh	218 /
Energy consumption (per year, based on standard test results) - average		kWh	/ 1340
Energy consumption (per year, based on standard test results) - warmer		kWh	/ 1279
Dehumidifying		Kg/h	2.500
Degree of protection (IN) / (OUT)		(IP)	IPX0/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	2400
Max. current		A	12
Compressor	Model		C-1RZ140H3DDF
	Type		Rotary
	Brand		SANYO
Indoor	Indoor Air Circulation	m ³ /h	1000
	Indoor Noise Level dB	dB(A)	56
	Net Dimension	mm	1089×328×227
	Packing Dimension	mm	1155×397×312
	Net Weight / Gross Weight	Kg	13,5
Outdoor	Outdoor Noise Level dB	dB(A)	56
	Net Dimension	mm	785×555×300
	Packing Dimension	mm	903×615×382
	Net Weight / Gross Weight	Kg	28,5
	Refrigerant Type		R32
	Refrigerant Weight	Kg	1,03
	GWP		675
	tCO ₂ eq.		0,70
	Max. Discharge / Max. Suction pressure	Mpa	4.3/2.5
Refrigerant piping	Liquid side / Gas side / Length	mm	Dg4/Dg10(1/4-1/2)
	Max. refrigerant pipe length / Max. difference in level	m	25/15