



Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low Temperature Heating/Cooling, Honeycomb filter, Washable filter, High density filter, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Horizontal louver auto swing, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, Horizontal swing, RC holder, Additional Health filter, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Wi Fi, Additional Health filter, Tray Heater

Capacity			24000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			Cooling Heating
Rated capacity		W	7200(1800-7400) 7300(1800-800)
Power input		W	1700(230-2300) 2300(230-2530)
Current input		A	7.9(1-10) 10.5(1-11)
SEER / Energy Class			8,5/A+++ /
SCOP / Energy Class - average			/ 4,6/A++
SCOP / Energy Class - warmer			/ 5,4/A+++
Operating range (°C)		°C	15-53 -25-32
Energy consumption (per year, based on standard test results)		kWh	252 /
Energy consumption (per year, based on standard test results) - average		kWh	/ 1644
Energy consumption (per year, based on standard test results) - warmer		kWh	/ 1763
Dehumidifying		Kg/h	3100
Degree of protection (IN) / (OUT)		(IP)	IPX0/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	3200
Max. current		A	16
Compressor		Model	KTN150D53UFZC3
		Type	Rotary
		Brand	GMCC
Indoor	Indoor Air Circulation	m ³ /h	1300
	Indoor Noise Level dB	dB(A)	62
	Net Dimension	mm	1089×328×227
	Packing Dimension	mm	1155×397×312
	Net Weight / Gross Weight	Kg	13
Outdoor	Outdoor Noise Level dB	dB(A)	62
	Net Dimension	mm	900×700×350
	Packing Dimension	mm	1015×762×425
	Net Weight / Gross Weight	Kg	41
	Refrigerant Type		R32
	Refrigerant Weight	Kg	1,2
	GWP		675
	tCO ₂ eq.		0,81
	Max. Discharge / Max. Suction pressure	Mpa	4.3/2.5
Refrigerant piping	Liquid side / Gas side / Length	mm	Dg4/Dg13(1/4-5/8)
	Max. refrigerant pipe length / Max. difference in level	m	25/15