



Features

I Feel / Follow me, Breeze away, ECO, Self-diagnostic, Intelligent defrosting, Intelligent dusting switch, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/of, Five-speed outdoor fan motor, Golden fin, Mono & multi compatibility, 8°C heating feature, Low-Temperature Heating/Cooling, Washable filter, High-density filter, Cold-catalyst filter, Low ambient kit, 1W Standby, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory function, Horizontal louver auto-swing, Hidden led display, Display ON/OFF, Rapid Cooling, and Rapid Heating, RC holder, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed, I-clean, Intelligent on-off, Auto Swing Louver function, Anti-Cold Air

| | | | |
|---|--|-------------------|-------------------|
| Capacity | | 12000BTU | |
| Rated volt and frequency | | 220-240V~/50HZ | |
| Mode | V/Hz | Cooling | Heating |
| Rated capacity | | 12000(4500~13500) | 13500(3000~15500) |
| Power input | W | 925(130~1250) | 990(120~1450) |
| Current input | W | 3.9(0.6~5.55) | 4.4(0.6~6.4) |
| SEER-/ Energy Class | A | 8,5/A+++ | / |
| SCOP/ Energy Class - average | | / | 4,6/A++ |
| SCOP/ Energy Class - warmer | | / | 6,0/A+++ |
| Operating range | | 15-50 | -25-24 |
| Energy consumption (per year, based on standard test results) | °C | 150 | / |
| Energy consumption (per year, based on standard test results) - average | kWh | / | 815 |
| Energy consumption (per year, based on standard test results) - warmer | kWh | / | 678 |
| Dehumidifying | Kg/h | 1,7 | |
| Degree of protection (IN) / (OUT) | (IP) | IPX0/IPX4 | |
| Class of electric protection (IN) / (OUT) | Class I / Class II | I/I | |
| Max. input consumption | W | 2200 | |
| Max. current | A | 10,5 | |
| Compressor | Model | KSN98D64UFZ3 | |
| | Type | Rotary | |
| | Brand | GMCC | |
| Indoor | Indoor Air Circulation | m³/h | 560 |
| | Indoor Noise Level dB | dB(A) | 41/34/22/21 |
| | Net Dimension | mm | 795x225x295 |
| | Packing Dimension | mm | 870x370x305 |
| | Net Weight/Gross Weight | Kg | 10,2/14,7 |
| Outdoor | Outdoor Noise Level dB | dB(A) | 59 |
| | Net Dimension | mm | 765x303x555 |
| | Packing Dimension | mm | 887x337x610 |
| | Net Weight/Gross Weight | Kg | 26.4/28.7 |
| | Refrigerant type | | R32 |
| | Refrigerant weight | Kg | 0,62 |
| | GWP | | 675 |
| | tCO ₂ eq. | | 0,41 |
| Max. Discharge/Max. Suction pressure | Mpa | 4.3/1.7 | |
| Refrigerant piping | Liquid side/ Gas side/Length | mm | Dg4/Dg8 (1/4-3/8) |
| | Max. refrigerant pipe length/ Max. difference in level | m | 25/10 |