R32 Inverter Split Type Model
TT27TP81-0932IHWT

Features

I Feel / Follow me, Breeze away, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low Temperature Heating/Cooling, Honeycomb filter, Washable filter, High density filter, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Horizontal louver auto swing, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, Horizontal swing, RC holder, Additional Health filter, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Wi Fi, Additional Health filter, Energy Efficiance, Tray Heater

Capacity				9000BTU	
Rated volt and frequency			**V/Hz**	220-240V~/50Hz/1P	
Mode				**Cooling**	**Heating**
Rated capacity			**W**	2610(940~3700)	3320(940~4000)
Power input			**W**	672(240~1380)	860(240~1552)
Current input			**A**	3.0(1.2~8.1)	3.9(1.2~9.0)
SEER / Energy Class				8,5 A+++	/
SCOP / Energy Class - average				/	4,6/A++
SCOP / Energy Class - warmer				/	5,2/A+++
Operating range (°C)			**°C**	15-52	-25-30
Energy consumption (per year, based on standard test results)			**kWh**	108	/
Energy consumption (per year, based on standard test results) - average			**kWh**	/	731
Energy consumption (per year, based on standard test results) - warmer			**kWh**	/	674
Dehumidifying			**Kg/h**	1,2	
Degree of protection (IN) / (OUT)			**(IP)**	IPX0/IPX4	
Class of electric protection (IN) / (OUT)			**Class I / Class II**	I/I	
Max. input consumption			**W**	1552	
Max. current			**A**	9	
Compressor		**Model**		KSN89D28UDZW31	
		Type		Rotary	
		Brand		GMCC	
Indoor	Indoor Air Circulation		m^3/h	680	
	Indoor Noise Level dB		dB(A)	44/41/37/34/29/25/19	
	Net Dimension		mm	820×306×195	
	Packing Dimension		mm	890×380×265	
	Net Weight / Gross Weight		Kg	9/11	
Outdoor	Outdoor Noise Level dB		dB(A)	62	
	Net Dimension		mm	787×498×290	
	Packing Dimension		mm	818×520×325	
	Net Weight / Gross Weight		Kg	22/24	
	Refrigerant Type			R32	
	Refrigerant Weight		Kg	0,57	
	GWP			675	
	$tCO_2eq.$			0,38	
	Max. Discharge / Max. Suction pressure		Mpa	4.3/2.5	
Refrigerant piping		Liquid side / Gas side / Length	mm	Dg4/Dg8(1/4-3/8)	
		Max. refrigerant pipe length / Max. difference in level	m	25/10	