



Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low Temperature Heating/Cooling, Honeycomb filter, Washable filter, High density filter, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Horizontal louver auto swing, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, Horizontal swing, RC holder, Additional Health filter, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Wi Fi, Additional Health filter, Energy Efficiency, Tray Heater

Capacity		9000BTU	
Rated volt and frequency		V/Hz 220-240V~/50Hz/1P	
Mode		Cooling	Heating
Rated capacity	W	2610(940~3700)	3320(940~4000)
Power input	W	672(240~1380)	860(240~1552)
Current input	A	3.0(1.2~8.1)	3.9(1.2~9.0)
SEER / Energy Class		8,5 A+++	/
SCOP / Energy Class - average		/	4,6/A++
SCOP / Energy Class - warmer		/	5,2/A+++
Operating range (°C)		°C 15-52	-25-30
Energy consumption (per year, based on standard test results)		kWh 108	/
Energy consumption (per year, based on standard test results) - average		kWh /	731
Energy consumption (per year, based on standard test results) - warmer		kWh /	674
Dehumidifying		Kg/h 1,2	
Degree of protection (IN) / (OUT)		(IP) IPX0/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II I/I	
Max. input consumption		W 1552	
Max. current		A 9	
Compressor		Model	KSN89D28UDZW31
		Type	Rotary
		Brand	GMCC
Indoor	Indoor Air Circulation	m ³ /h	680
	Indoor Noise Level dB	dB(A)	54/50/47/44/39/35/29
	Net Dimension	mm	820×306×195
	Packing Dimension	mm	890×380×265
	Net Weight / Gross Weight	Kg	9/11
Outdoor	Outdoor Noise Level dB	dB(A)	62
	Net Dimension	mm	787×498×290
	Packing Dimension	mm	818×520×325
	Net Weight / Gross Weight	Kg	22/24
	Refrigerant Type		R32
	Refrigerant Weight	Kg	0,57
	GWP		675
	tCO ₂ eq.		0,38
	Max. Discharge / Max. Suction pressure	Mpa	4.3/2.5
Refrigerant piping	Liquid side / Gas side / Length	mm	Dg4/Dg8(1/4-3/8)
	Max. refrigerant pipe length / Max. difference in level	m	25/10