



Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low Temperature Heating/Cooling, Honeycomb filter, Washable filter, High density filter, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Horizontal louver auto swing, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, Horizontal swing, RC holder, Additional Health filter, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Wi Fi, Additional Health filter, Energy Efficiency, Tray Heater

| | | | |
|--|---|--------------------|-----------------------------------|
| Capacity | | | 18000BTU |
| Rated volt and frequency | | V/Hz | 220-240V~/50Hz/1P |
| Mode | | | Cooling Heating |
| Rated capacity | W | 5200(1250~5920) | 5500(1250~6690) |
| Power input | W | 1417(330-2350) | 1401(340-2540) |
| Current input | A | 6.4(1.7~12.0) | 6.4(1.7~13.0) |
| SEER / Energy Class | | 8,5 A+++ | / |
| SCOP / Energy Class - average | | / | 4,6/A++ |
| SCOP / Energy Class - warmer | | / | 5,6/A+++ |
| Operating range (°C) | | °C | 15-52 -25-30 |
| Energy consumption (per year, based on standard test results) | | kWh | 215 / |
| Energy consumption (per year, based on standard test results) - average | | kWh | / 1279 |
| Energy consumption (per year, based on standard test results) - warmer | | kWh | / 1250 |
| Dehumidifying | | Kg/h | 1,8 |
| Degree of protection (IN) / (OUT) | | (IP) | IPX0/IPX4 |
| Class of electric protection (IN) / (OUT) | | Class I / Class II | I/I |
| Max. input consumption | | W | 2540 |
| Max. current | | A | 13 |
| Compressor | | Model | C-1RZ140H3CBF |
| | | Type | Rotary |
| | | Brand | SANYO |
| Indoor | Indoor Air Circulation | m ³ /h | 900 |
| | Indoor Noise Level dB | dB(A) | 57/52/50/48/46/44/42 |
| | Net Dimension | mm | 920×306×195 |
| | Packing Dimension | mm | 990×380×265 |
| | Net Weight / Gross Weight | Kg | 10/13 |
| Outdoor | Outdoor Noise Level dB | dB(A) | 65 |
| | Net Dimension | mm | 927×699×380 |
| | Packing Dimension | mm | 949×732×392 |
| | Net Weight / Gross Weight | Kg | 38/41 |
| | Refrigerant Type | | R32 |
| | Refrigerant Weight | Kg | 0,87 |
| | GWP | | 675 |
| | tCO ₂ eq. | | 0,59 |
| | Max. Discharge / Max. Suction pressure | Mpa | 4.3/2.5 |
| Refrigerant piping | Liquid side / Gas side / Length | mm | Dg4/Dg8(1/4-1/2) |
| | Max. refrigerant pipe length / Max. difference in level | m | 25/10 |