



## Features

I Feel / Follow me, Breeze away, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low Temperature Heating/Cooling, Honeycomb filter, Washable filter, High density filter, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Horizontal louver auto swing, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, Horizontal swing, RC holder, Additional Health filter, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Wi Fi, Additional Health filter, Energy Efficiency, Tray Heater

Capacity			24000BTU
Rated volt and frequency		V/Hz	220-240V~/50Hz/1P
Mode			Cooling Heating
Rated capacity		W	7000(1830~7820)7100(1850~7960)
Power input		W	1940(410~2830)1810(420~3010)
Current input		A	8.7(2.3~15.5)8.0(2.3~16.0)
SEER / Energy Class			8,5 A+++ /
SCOP / Energy Class - average			/ 4,7/A++
SCOP / Energy Class - warmer			/ 5,6/A+++
Operating range (°C)		°C	15-52-25-30
Energy consumption (per year, based on standard test results)		kWh	289 /
Energy consumption (per year, based on standard test results) - average		kWh	/ 1579
Energy consumption (per year, based on standard test results) - warmer		kWh	/ 1600
Dehumidifying		Kg/h	2
Degree of protection (IN) / (OUT)		(IP)	IPX0/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	3010
Max. current		A	16
Compressor	Model		C-6RZ180H3AAF
	Type		Rotary
	Brand		SANYO
Indoor	Indoor Air Circulation	m³/h	1150
	Indoor Noise Level dB	dB(A)	50/44/40/37/34/30/26
	Net Dimension	mm	1100×333×222
	Packing Dimension	mm	1165×405×295
	Net Weight / Gross Weight	Kg	14/17
Outdoor	Outdoor Noise Level dB	dB(A)	68
	Net Dimension	mm	978×803×421
	Packing Dimension	mm	1022×835×480
	Net Weight / Gross Weight	Kg	45/49,5
	Refrigerant Type		R32
	Refrigerant Weight	Kg	1,27
	GWP		675
	tCO <sub>2</sub> eq.		0,86
	Max. Discharge / Max. Suction pressure	Mpa	4.3/2.5
Refrigerant piping		Liquid side / Gas side / Length	mmDg4/Dg8(1/4-1/2)
		Max. refrigerant pipe length / Max. difference in level	m25/10