



Console IDU			TAIF-09DW	TAIF-12DW	TAIF-18DW
Capacity	Cooling	Btu/h	8872(5120-12115)	12285(5800-12625)	16036(8530-16378)
		kW	2.60(1.50-3.55)	3.50(1.70-3.70)	4.70(2.50-4.80)
	Heating	Btu/h	9560(5120-12115)	12625(5120-12625)	17060(8530-19107)
		kW	2.80(1.50-3.55)	3.50(1.50-3.70)	5.0(2.50-5.6)
Electric Data	Power Supply	V~,Hz,Ph	220~240,50,1	220~240,50,1	220~240,50,1
	Cooling Power Input	W	40(20-65)	40(20-65)	55(20-80)
	Cooling Rated Current	A	0,17	0,17	0,24
	Heating Power Input	W	40(20-65)	40(20-65)	55(20-80)
	Heating Rated Current	A	0,17	0,17	0,24
Fan Motor	Model		RD35HA	RD35HA	RD35HA
	Brand		wolong	wolong	wolong
	Output Power	W	35	35	35
	Capacitor	uF	/	/	/
	Speed	r/min	650	650	690
Indoor Coil	Number Of Row		2	2	2
	Tube x Row Pitch	mm	21*13.37	21*13.37	21*13.37
	Fin Pitch	mm	1.3	1.3	1.3
	Fin Material		Hydrophilic	Hydrophilic	Hydrophilic
	Tube Dia.& Material	mm	φ7, Inner grooved	φ7, Inner grooved	φ7, Inner grooved
	Coil L x H x W	mm	515x399x26.74	515x399x26.74	515x399x26.74
	Heat Exchanging Area	m²	8,45	8,45	8,45
Performance	Air Volume	CFM	353/312/253	353/312/253	382/324/265
		m³/h	600/530/430	600/530/430	650/550/450
	Sound Pressure Noise Level	dB(A)	42/39/36	42/39/36	44/40/37
	Sound Power Noise Level	dB(A)	52	52	54
Dimension	Net Dimension (WxDxH)	mm	700x225x600	700x225x600	700x225x600
	Packing Dimension (WxDxH)	mm	780x300x675	780x300x675	780x300x675
Weight	Net	kg	15	15	15
	Gross	kg	19	19	19
Refrigerant Type			R32	R32	R32
Pipe Diameter	Liquid Side	mm	6.35(1/4)	6.35(1/4)	6.35(1/4)
	Gas Side	mm	9.52(3/8)	9.52(3/8)	9.52(3/8)
	Drainage	mm	20	20	20
Loading Qty	20/40/40H	unit	198/411/462	198/411/462	198/411/462