



Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low Temperature Heating/Cooling, Honeycomb filter, Washable filter, High density filter, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Horizontal louver auto swing, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, Horizontal swing, RC holder, Additional Health filter, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Wi Fi, Additional Health filter, Pipes and Cables

Capacity		18000BTU	
Rated volt and frequency	V/Hz	220-240V~/50HZ	
Mode		Cooling	Heating
Rated capacity	W	3500(800-3800)	3800(1000-4100)
Power input	W	1180(100-1400)	1120(300-1400)
Current input	A	5.5(0.7-7.8)	5.3(1.5-7.8)
SEER / Energy Class		6,2 A++	/
SCOP / Energy Class - average		/	4,0/A+
SCOP / Energy Class - warmer		/	5,1/A+++
Operating range (°C)	°C	15~49	-15~32
Energy consumption (per year, based on standard test results)	kWh	198	/
Energy consumption (per year, based on standard test results) - average	kWh	/	945
Energy consumption (per year, based on standard test results) - warmer	kWh	/	933
Dehumidifying	Kg/h	1,7	
Degree of protection (IN) / (OUT)	(IP)	IPX0/IPX4	
Class of electric protection (IN) / (OUT)	Class I / Class II	I/I	
Max. input consumption	W	1900	
Max. current	A	9,5	
Compressor	Model	KSN89D28UE4A31	
	Type	Rotary	
	Brand	GMCC	
Indoor	Indoor Air Circulation	m³/h	600
	Indoor Noise Level dB	dB(A)	53/48/44/42/29
	Net Dimension	mm	761×296×199
	Packing Dimension	mm	825×367×277
	Net Weight / Gross Weight	Kg	8/10,5
Outdoor	Outdoor Noise Level dB	dB(A)	62
	Net Dimension	mm	708×530×258
	Packing Dimension	mm	825×595×345
	Net Weight / Gross Weight	Kg	21/24
	Refrigerant Type		R32
Refrigerant piping	Refrigerant Weight	Kg	0,54
	GWP		675
	tCO₂eq.		0,36
	Max. Discharge / Max. Suction pressure	Mpa	4.3/2.5
	Liquid side / Gas side / Length	mm	Dg4/Dg8(1/4-3/8)
	Max. refrigerant pipe length / Max. difference in level	m	20/10