



Features

I Feel / Follow me, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low Temperature Heating/Cooling, Honeycomb filter, Washable filter, High density filter, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Horizontal louver auto swing, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, Horizontal swing, RC holder, Additional Health filter, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Wi Fi, Tray Heater

Capacity			18000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity		W	5400(1300-5900) 5800(1300-6100)	
Power input		W	14300(290-19500) 1.33(0.25-1.8)	
Current input		A	6.4(2.2-6.8) 6.1(2.0-8.0)	
SEER / Energy Class			8,7 A+++ /	
SCOP / Energy Class - average			/ 4,6/A++	
SCOP / Energy Class - warmer			/ 5,8/A+++	
Operating range (°C)		°C	15~53 -25~32	
Energy consumption (per year, based on standard test results)		kWh	215 /	
Energy consumption (per year, based on standard test results) - average		kWh	/ 1339	
Energy consumption (per year, based on standard test results) - warmer		kWh	/ 1303	
Dehumidifying		Kg/h	2,5	
Degree of protection (IN) / (OUT)		(IP)	IPX0/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	2400	
Max. current		A	12	
Compressor		Model	C-1RZ140H3DDF	
		Type	Rotary	
		Brand	SANYO	
Indoor	Indoor Air Circulation	m ³ /h	1060	
	Indoor Noise Level dB	dB(A)	56/51/47/44/31	
	Net Dimension	mm	1140×332×230	
	Packing Dimension	mm	1210×400×327	
	Net Weight / Gross Weight	Kg	13/17	
Outdoor	Outdoor Noise Level dB	dB(A)	62	
	Net Dimension	mm	785×548×281	
	Packing Dimension	mm	903×615×382	
	Net Weight / Gross Weight	Kg	28,5/32	
	Refrigerant Type		R32	
	Refrigerant Weight	Kg	1,03	
	GWP		675	
	tCO ₂ eq.		0,70	
Max. Discharge / Max. Suction pressure		Mpa	4.3/2.5	
Refrigerant piping		Liquid side / Gas side / Length	mm	Dg4/Dg8(1/4-3/8)
		Max. refrigerant pipe length / Max. difference in level	m	20/10