



## Features

4-fan speed, Turbo Mode, Anti-cold Air, Mute Mode, 8°C heating, Comfortable Cooling, Independent Dehumidification, Auto Mode, Display On/off, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Rust Proof, Rust Proof for indoor Evaporator pipes, Rust Proof for outdoor condenser pipes, Wide Voltage Range Start-up, Children Lock, Refrigerant leakage Detection, Compressor preheating, Auto-restart, Self-diagnosis, Louver Position Memory, Dual Drainage, Easy-washable Filter, I Set, Gold Fin, Hidden Display, Self-cleaning, Self-cleaning (Outdoor unit), Healthy Filter, Sleep Mode, ECO, Timer, GEN mode, AI Energy Saving 2.0, Low Temperature Heating ( -15°C), Holder RC, Valve Cover

<b>Capacity</b>		9000BTU	
<b>Rated volt and frequency</b>		V/Hz 220-240V~/50HZ	
<b>Mode</b>		<b>Cooling</b>	<b>Heating</b>
<b>Rated capacity</b>	W	2500W(300~3200)	2600W(300~3300)
<b>Power input</b>	W	800W(150~1300)	750W(150~1250)
<b>Current input</b>	A	3.6A(0.8~5.8)	3.4A(0.8~5.6)
<b>SEER / Energy Class</b>		6,1 A++	/
<b>SCOP / Energy Class - average</b>		/	4,0/A+
<b>SCOP / Energy Class - warmer</b>		/	5.1/A+++
<b>Operating range (°C)</b>	°C	16-32	
<b>Energy consumption (per year, based on standard test results)</b>	kWh	145	/
<b>Energy consumption (per year, based on standard test results) - average</b>	kWh	/	792
<b>Energy consumption (per year, based on standard test results) - warmer</b>	kWh	/	660
<b>Dehumidifying</b>	Kg/h	0,9	
<b>Degree of protection (IN) / (OUT)</b>	(IP)	IPX0/IPX4	
<b>Class of electric protection (IN) / (OUT)</b>	Class I / Class II	I/I	
<b>Max. input consumption</b>	W	1640	
<b>Max. current</b>	A	7.5	
<b>Compressor</b>	Model	LAMDA	
	Type	Rotary	
	Brand	FTz-AN075ACBA-A	
<b>Indoor</b>	Indoor Air Circulation	m <sup>3</sup> /h	500
	Indoor Noise Level dB	dB(A)	30-48
	Net Dimension	mm	680x252x215
	Packing Dimension	mm	750x312x272
	Net Weight / Gross Weight	Kg	7/8.5
<b>Outdoor</b>	Outdoor Noise Level dB	dB(A)	61
	Net Dimension	mm	720*299*473
	Packing Dimension	mm	777x333x530
	Net Weight / Gross Weight	Kg	18/21
	Refrigerant Type		R32
	Refrigerant Weight	Kg	0,39
	GWP		675
	tCO <sub>2</sub> eq.		0,26
<b>Max. Discharge / Max. Suction pressure</b>	Mpa	4.2/1.9	
<b>Refrigerant piping</b>	Liquid side / Gas side / Length	mm	Dg4/Dg8(1/4-3/8)
	Max. refrigerant pipe length / Max. difference in level	m	15/5