



Features

4-fan speed, Turbo Mode, Anti-cold Air, Mute Mode, 8°C heating, Comfortable Cooling, Independent Dehumidification, Auto Mode, Display On/off, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Rust Proof, Rust Proof for indoor Evaporator pipes, Rust Proof for outdoor condensor pipes, Wide Voltage Range Start-up, Children Lock, Refrigerant leakage Detection, Compressor preheating, Auto-restart, Self-diagnosis, Louver Position Memory, Dual Drainage, Easy-washable Filter, I Set, Gold Fin, Hidden Display, Self-cleaning, Self-cleaning (Outdoor unit), Healthy Filter, Sleep Mode, ECO, Timer, GEN mode, AI Energy Saving 2.0, Low Temperature Heating (-15°C), Holder RC, Valve Cover, 4D Air Flow, Photocatalysis file, Wi Fi, Hotel menu, I Feel, photocatalysis, Tray heater

| | | | |
|--|--|---------------------------|-----------------|
| Capacity | | 18000BTU | |
| Rated volt and frequency | | V/Hz 220-240V~/50HZ | |
| Mode | | Cooling | Heating |
| Rated capacity | W | 5200(700~5400) | 5300(700~5600) |
| Power input | W | 1530(210~1610) | 1350(210~1570) |
| Current input | A | 6.9(1.2~7.2) | 6.1(1.2~7.0) |
| SEER / Energy Class | | 6,5 A++ | / |
| SCOP / Energy Class - average | | / | 4,2 /A+ |
| SCOP / Energy Class - warmer | | / | 5.1/A+++ |
| Operating range (°C) | | °C 16-32 | |
| Energy consumption (per year, based on standard test results) | | kWh 280 | / |
| Energy consumption (per year, based on standard test results) - average | | kWh / | 1417 |
| Energy consumption (per year, based on standard test results) - warmer | | kWh / | 1395 |
| Dehumidifying | | Kg/h 1,8 | |
| Degree of protection (IN) / (OUT) | | (IP) IPX0/IPX4 | |
| Class of electric protection (IN) / (OUT) | | Class I / Class II I/I | |
| Max. input consumption | | W 24502450 | |
| Max. current | | A 1111 | |
| Compressor | | Model | GMCC/LAMDA |
| | | Type | Rotary |
| | | Brand | FTz-AN125AFBA-A |
| Indoor | Indoor Air Circulation | m ³ /h 1000 | |
| | Indoor Noise Level dB | dB(A) 35-53 | |
| | Net Dimension | mm 910×295×220 | |
| | Packing Dimension | mm 985×370×304 | |
| | Net Weight / Gross Weight | Kg 12/14 | |
| Outdoor | Outdoor Noise Level dB | dB(A) 64 | |
| | Net Dimension | mm 728×262×540 | |
| | Packing Dimension | mm 850×347×592 | |
| | Net Weight / Gross Weight | Kg 26/30 | |
| | Refrigerant Type | R32 | |
| | Refrigerant Weight | Kg 0,86 | |
| | GWP | 675 | |
| | tCO₂eq. | 0,58 | |
| Max. Discharge / Max. Suction pressure | | Mpa 4.2/1.9 | |
| Refrigerant piping | Liquid side / Gas side / Length | mm Dg4/Dg8(1/4-3/8) | |
| | Max. refrigerant pipe length / Max. difference in level | m 15/5 | |