



Features

4-fan speed, Turbo Mode, Anti-cold Air, Mute Mode, 8°C heating, Comfortable Cooling, Independent Dehumidification, Auto Mode, Display On/off, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Rust Proof, Rust Proof for indoor Evaporator pipes, Rust Proof for outdoor condenser pipes, Wide Voltage Range Start-up, Children Lock, Refrigerant leakage Detection, Compressor preheating, Auto-restart, Self-diagnosis, Louver Position Memory, Dual Drainage, Easy-washable Filter, I Set, Gold Fin, Hidden Display, Self-cleaning, Self-cleaning (Outdoor unit), Healthy Filter, Sleep Mode, ECO, Timer, GEN mode, AI Energy Saving 2.0, Low Temperature Heating (-15°C), Holder RC, Valve Cover, 4D Air Flow, Photocatalysis file, Wi Fi, Hotel menu, I Feel, photocatalysis, Tray heater

Capacity		24000BTU	
Rated volt and frequency		V/Hz 220-240V~/50HZ	
Mode		Cooling	Heating
Rated capacity	W	7000(700~7200)	7100(700~7300)
Power input	W	2150(210~2220)	1890(210~2050)
Current input	A	9.6(1.2~10.0)	8.5(1.2~9.2)
SEER / Energy Class		6,5 A++	/
SCOP / Energy Class - average		/	4,2 /A+
SCOP / Energy Class - warmer		/	5.1/A+++
Operating range (°C)		°C 16-32	
Energy consumption (per year, based on standard test results)		kWh 376	/
Energy consumption (per year, based on standard test results) - average		kWh /	1777
Energy consumption (per year, based on standard test results) - warmer		kWh /	1647
Dehumidifying		Kg/h 2,4	
Degree of protection (IN) / (OUT)		(IP) IPX0/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II I/I	
Max. input consumption		W 30003000	
Max. current		A 1414	
Compressor	Model		
	Type	GMCC Rotary	
	Brand	KTN150D42UFZ	
Indoor	Indoor Air Circulation	m ³ /h	1100
	Indoor Noise Level dB	dB(A)	35-54
	Net Dimension	mm	910×295×220
	Packing Dimension	mm	985×370×304
	Net Weight / Gross Weight	Kg	13/15
Outdoor	Outdoor Noise Level dB	dB(A)	65
	Net Dimension	mm	835×322×546
	Packing Dimension	mm	934×382×608
	Net Weight / Gross Weight	Kg	30/34
	Refrigerant Type		R32
	Refrigerant Weight	Kg	1,2
	GWP		675
	tCO ₂ eq.		0,81
Max. Discharge / Max. Suction pressure		Mpa	4.2/1.9
Refrigerant piping	Liquid side / Gas side / Length	mm	Dg4/Dg8(1/4-4/8)
	Max. refrigerant pipe length / Max. difference in level	m	15/5