



Features

4-fan speed, Turbo Mode, Anti-cold Air, Mute Mode, 8°C heating, Comfortable Cooling, Independent Dehumidification, Auto Mode, Display On/off, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Rust Proof, Rust Proof for indoor Evaporator pipes, Rust Proof for outdoor condenser pipes, Wide Voltage Range Start-up, Children Lock, Refrigerant leakage Detection, Compressor preheating, Auto-restart, Self-diagnosis, Louver Position Memory, Dual Drainage, Easy-washable Filter, I Set, Gold Fin, Hidden Display, Self-cleaning, Self-cleaning (Outdoor unit), Healthy Filter, Sleep Mode, ECO, Timer, GEN mode, AI Energy Saving 2.0, Low Temperature Heating (-15°C), Holder RC, Valve Cover

Capacity		24000BTU	
Rated volt and frequency		V/Hz 220-240V~/50HZ	
Mode		Cooling	Heating
Rated capacity	W	6500W(600W~6600W)	6500W(600W~6800W)
Power input	W	2000W(210W~2180W)	1850W(210W~2050W)
Current input	A	9.2A(1.2A~10A)	8.5A(1.2A~9.4A)
SEER / Energy Class		6,1 A++	/
SCOP / Energy Class - average		/	4,0/A+
SCOP / Energy Class - warmer		/	5.1/A+++
Operating range (°C)	°C	16-32	
Energy consumption (per year, based on standard test results)	kWh	347	/
Energy consumption (per year, based on standard test results) - average	kWh	/	1835
Energy consumption (per year, based on standard test results) - warmer	kWh	/	1585
Dehumidifying	Kg/h	2,4	
Degree of protection (IN) / (OUT)	(IP)	IPX0/IPX4	
Class of electric protection (IN) / (OUT)	Class I / Class II	I/I	
Max. input consumption	W	30003000	
Max. current	A	1414	
Compressor	Model		
	Type	GMCC	
	Brand	Rotary	
		KTN150D42UFZ	
Indoor	Indoor Air Circulation	m ³ /h	1000
	Indoor Noise Level dB	dB(A)	42-54
	Net Dimension	mm	954X314X245
	Packing Dimension	mm	1025×385×310
	Net Weight / Gross Weight	Kg	14/17
Outdoor	Outdoor Noise Level dB	dB(A)	65
	Net Dimension	mm	898×345×546
	Packing Dimension	mm	934×382×608
	Net Weight / Gross Weight	Kg	30/33
	Refrigerant Type		R32
	Refrigerant Weight	Kg	1,2
	GWP		675
	tCO ₂ eq.		0,81
Max. Discharge / Max. Suction pressure	Mpa	4.2/1.9	
Refrigerant piping	Liquid side / Gas side / Length	mm	Dg4/Dg8(1/4-4/8)
	Max. refrigerant pipe length / Max. difference in level	m	15/5