



Features

5-Fan Speed: Mute/Low/Mid/High/Turbo, Turbo Mode, Anti-cold Air, Mute Mode, 8°C heating, I Feel, Low Temperature Cooling (-15°C), Comfortable Cooling, Independent Dehumidification, Auto Mode, Display On/off, Smart Airflow, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Rust Proof, Wide Voltage Range Start-up, Child Lock, Cooling at 53°C, Refrigerant leakage Detection, Auto-restart, Self-diagnosis, Backlight Display remote control, Louver Position Memory, Dual Drainage, Easy-washable Filter, I Set, Hidden Display, Self-cleaning, Sleep Mode, ECO, Timer, GEN mode, Horizontal swing, 4D Air Flow, Holder RC, Wi Fi, Active Carbon filter

Capacity			12000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			Cooling Heating
Rated capacity		W	3400(1000~3770) 3420(1000~3810)
Power input		W	1130(290~1500) 1005(290~1720)
Current input		A	5.8(1.5~9.0) 5.1(1.5~10.0)
SEER / Energy Class			6,1 A++ /
SCOP / Energy Class - average			/ 4,0/A+
SCOP / Energy Class - warmer			/ 5,1 A+++
Operating range (°C)		°C	17-53°C -20-30°C
Energy consumption (per year, based on standard test results)		kWh	195 /
Energy consumption (per year, based on standard test results) - average		kWh	/ 735
Energy consumption (per year, based on standard test results) - warmer		kWh	/ 631
Dehumidifying		Kg/h	1,2
Degree of protection (IN) / (OUT)		(IP)	IPX0/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	1720
Max. current		A	10
Compressor		Model	35W2ALLB9F#MC
		Type	Rotary
		Brand	REICHI
Indoor	Indoor Air Circulation	m³/h	560
	Indoor Noise Level dB	dB(A)	51/47/43/35/32
	Net Dimension	mm	790×275×192
	Packing Dimension	mm	860×345×265
	Net Weight / Gross Weight	Kg	8/10
Outdoor	Outdoor Noise Level dB	dB(A)	60
	Net Dimension	mm	712×276×459
	Packing Dimension	mm	765×310×481
	Net Weight / Gross Weight	Kg	22/24
	Refrigerant Type		R32
	Refrigerant Weight	Kg	0,49
	GWP		675
	tCO ₂ eq.		0,33
	Max. Discharge / Max. Suction pressure	Mpa	4.3/2.5
Refrigerant piping	Liquid side / Gas side / Length	mm	Dg4/Dg8(1/4-3/8)
	Max. refrigerant pipe length / Max. difference in level	m	25/10