



## Features

5-Fan Speed: Mute/Low/Mid/High/Turbo, Turbo Mode, Anti-cold Air, Mute Mode, 8°C heating, I Feel, Low Temperature Cooling (-15°C), Comfortable Cooling, Independent Dehumidification, Auto Mode, Display On/off, Smart Airflow, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Rust Proof, Wide Voltage Range Start-up, Child Lock, Cooling at 53°C, Refrigerant leakage Detection, Auto-restart, Self-diagnosis, Backlight Display remote control, Louver Position Memory, Dual Drainage, Easy-washable Filter, I Set, Hidden Display, Self-cleaning, Sleep Mode, ECO, Timer, GEN mode, Holder RC

<b>Capacity</b>		18000BTU	
<b>Rated volt and frequency</b>	V/Hz	220-240V~/50HZ	
<b>Mode</b>		<b>Cooling</b>	<b>Heating</b>
<b>Rated capacity</b>	W	5100(1250-5910)	5100(1250-6070)
<b>Power input</b>	W	1580(330-2340)	1374(340-2520)
<b>Current input</b>	A	8.1(1.7~12.0)	7.0(1.7~13.0)
<b>SEER / Energy Class</b>		6,1 A++	/
<b>SCOP / Energy Class - average</b>		/	4,0/A+
<b>SCOP / Energy Class - warmer</b>		/	5,1 A+++
<b>Operating range (°C)</b>	°C	17-53°C	-20-30°C
<b>Energy consumption (per year, based on standard test results)</b>	kWh	293	/
<b>Energy consumption (per year, based on standard test results) - average</b>	kWh	/	1330
<b>Energy consumption (per year, based on standard test results) - warmer</b>	kWh	/	1373
<b>Dehumidifying</b>	Kg/h	1,5	
<b>Degree of protection (IN) / (OUT)</b>	(IP)	IPX0/IPX4	
<b>Class of electric protection (IN) / (OUT)</b>	Class I / Class II	I/I	
<b>Max. input consumption</b>	W	2520	
<b>Max. current</b>	A	13	
<b>Compressor</b>	Model		
	Type	Rotary	
	Brand	GMCC	
<b>Indoor</b>	Indoor Air Circulation	m³/h	800
	Indoor Noise Level dB	dB(A)	53/50/47/43/36
	Net Dimension	mm	910×294×206
	Packing Dimension	mm	979×372×277
	Net Weight / Gross Weight	Kg	10/13
<b>Outdoor</b>	Outdoor Noise Level dB	dB(A)	65
	Net Dimension	mm	853×602×349
	Packing Dimension	mm	890×628×385
	Net Weight / Gross Weight	Kg	31/34
	Refrigerant Type		R32
	Refrigerant Weight	Kg	1,00
	GWP		675
	tCO <sub>2</sub> eq.		0,68
<b>Max. Discharge / Max. Suction pressure</b>	Mpa	4.3/2.5	
<b>Refrigerant piping</b>	Liquid side / Gas side / Length	mm	Dg4/Dg8(1/4-3/8)
	Max. refrigerant pipe length / Max. difference in level	m	25/10