R32 Inverter Split Type Model
TD68TD2-2432IA

Features

5-Fan Speed: Mute/Low/Mid/High/Turbo, Turbo Mode, Anti-cold Air, Mute Mode, 8°C heating, I Feel, Low Temperature Cooling (-20°C), Comfortable Cooling, Independent Dehumidification, Auto Mode, Display On/off, Smart Airflow, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Rust Proof, Wide Voltage Range Start-up, Child Lock, Cooling at 53°C, Refrigerant leakage Detection, Auto-restart, Self-diagnosis, Backlight Display remote control, Louver Position Memory, Dual Drainage, Easy-washable Filter, I Set, Hidden Display, Self-cleaning, Sleep Mode, ECO, Timer, GEN mode, Holder RC

Capacity				24000BTU	
Rated volt and frequency			**V/Hz**	220-240V~/50HZ	
Mode				**Cooling**	**Heating**
Rated capacity			**W**	6810(1830~7800)	6870(1850~7900)
Power input			**W**	2257(410~2824)	2063(420~3005)
Current input			**A**	10.7(2.3~12.3)	9.9(2.3~13.5)
SEER / Energy Class				6,1 A++	/
SCOP / Energy Class - average				/	4,0/A+
SCOP / Energy Class - warmer				/	5,1 A+++
Operating range (°C)			**°C**	17-53°C	-20-30°C
Energy consumption (per year, based on standard test results)			**kWh**	390	/
Energy consumption (per year, based on standard test results) - average			**kWh**	/	1680
Energy consumption (per year, based on standard test results) - warmer			**kWh**	/	1592
Dehumidifying			**Kg/h**	1,8	
Degree of protection (IN) / (OUT)			**(IP)**	IPX0/IPX4	
Class of electric protection (IN) / (OUT)			**Class I / Class II**	I/I	
Max. input consumption			**W**	3005	
Max. current			**A**	13,5	
Compressor		Model			
		Type		Rotary	
		Brand		SANYO	
Indoor	Indoor Air Circulation		**m³/h**	980	
	Indoor Noise Level dB		**dB(A)**	54/51/48/44/40	
	Net Dimension		**mm**	1010×315×220	
	Packing Dimension		**mm**	1096×390×297	
	Net Weight / Gross Weight		**Kg**	13/16	
Outdoor	Outdoor Noise Level dB		**dB(A)**	67	
	Net Dimension		**mm**	920×699×380	
	Packing Dimension		**mm**	960×732×400	
	Net Weight / Gross Weight		**Kg**	40/43	
	Refrigerant Type			R32	
	Refrigerant Weight		**Kg**	1,14	
	GWP			675	
	$tCO_2eq.$			0,77	
	Max. Discharge / Max. Suction pressure		**Mpa**	4.3/2.5	
Refrigerant piping		Liquid side / Gas side / Length	**mm**	Dg4/Dg8(1/4-1/2)	
		Max. refrigerant pipe length / Max. difference in level	**m**	25/10	