



Features

5-Fan Speed: Mute/Low/Mid/High/Turbo, Turbo Mode, Anti-cold Air, Mute Mode, 8°C heating, I Feel, Low Temperature Cooling (-15°C), Comfortable Cooling, Independent Dehumidification, Auto Mode, Display On/off, Smart Airflow, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Rust Proof, Wide Voltage Range Start-up, Child Lock, Cooling at 53°C, Refrigerant leakage Detection, Auto-restart, Self-diagnosis, Backlight Display remote control, Louver Position Memory, Dual Drainage, Easy-washable Filter, I Set, Hidden Display, Self-cleaning, Sleep Mode, ECO, Timer, GEN mode, Holder RC

Capacity		24000BTU	
Rated volt and frequency	V/Hz	220-240V~/50HZ	
Mode		Cooling	Heating
Rated capacity	W	6810(1830~7800)	6870(1850~7900)
Power input	W	2257(410~2824)	2063(420~3005)
Current input	A	10.7(2.3~12.3)	9.9(2.3~13.5)
SEER / Energy Class		6,1 A++	/
SCOP / Energy Class - average		/	4,0/A+
SCOP / Energy Class - warmer		/	5,1 A+++
Operating range (°C)	°C	17-53°C	-20-30°C
Energy consumption (per year, based on standard test results)	kWh	390	/
Energy consumption (per year, based on standard test results) - average	kWh	/	1680
Energy consumption (per year, based on standard test results) - warmer	kWh	/	1592
Dehumidifying	Kg/h	1,8	
Degree of protection (IN) / (OUT)	(IP)	IPX0/IPX4	
Class of electric protection (IN) / (OUT)	Class I / Class II	I/I	
Max. input consumption	W	3005	
Max. current	A	13,5	
Compressor	Model		
	Type	Rotary	
	Brand	SANYO	
Indoor	Indoor Air Circulation	m ³ /h	980
	Indoor Noise Level dB	dB(A)	54/51/48/44/40
	Net Dimension	mm	1010×315×220
	Packing Dimension	mm	1096×390×297
	Net Weight / Gross Weight	Kg	13/16
Outdoor	Outdoor Noise Level dB	dB(A)	67
	Net Dimension	mm	920×699×380
	Packing Dimension	mm	960×732×400
	Net Weight / Gross Weight	Kg	40/43
	Refrigerant Type		R32
	Refrigerant Weight	Kg	1,14
	GWP		675
	tCO ₂ eq.		0,77
Max. Discharge / Max. Suction pressure	Mpa	4.3/2.5	
Refrigerant piping	Liquid side / Gas side / Length	mm	Dg4/Dg8(1/4-1/2)
	Max. refrigerant pipe length / Max. difference in level	m	25/10