



## Features

5-Fan Speed: Mute/Low/Mid/High/Turbo, Turbo Mode, Anti-cold Air, Mute Mode, 8°C heating, I Feel, Low Temperature Cooling (-15°C), Comfortable Cooling, Independent Dehumidification, Auto Mode, Display On/off, Smart Airflow, Rapid Cooling and Rapid Heating, Intelligent defrost, Emergency Button, Rust Proof, Wide Voltage Range Start-up, Child Lock, Cooling at 53°C, Refrigerant leakage Detection, Auto-restart, Self-diagnosis, Backlight Display remote control, Louver Position Memory, Dual Drainage, Easy-washable Filter, I Set, Hidden Display, Self-cleaning, Sleep Mode, ECO, Timer, GEN mode, Horizontal swing, 4D Air Flow, Holder RC, Wi Fi, Active Carbon filter

<b>Capacity</b>		24000BTU	
<b>Rated volt and frequency</b>	V/Hz	220-240V~/50HZ	
<b>Mode</b>		<b>Cooling</b>	<b>Heating</b>
<b>Rated capacity</b>	W	6840(1830~7820)	7050(1850~7960)
<b>Power input</b>	W	2099(410~2800)	1900(420~3000)
<b>Current input</b>	A	9.8(2.3~13.0)	8.6(2.3~14.0)
<b>SEER / Energy Class</b>		6,5 A++	/
<b>SCOP / Energy Class - average</b>		/	4,0/A+
<b>SCOP / Energy Class - warmer</b>		/	5,1 A+++
<b>Operating range (°C)</b>	°C	17-53°C	-20-30°C
<b>Energy consumption (per year, based on standard test results)</b>	kWh	366	/
<b>Energy consumption (per year, based on standard test results) - average</b>	kWh	/	1995
<b>Energy consumption (per year, based on standard test results) - warmer</b>	kWh	/	1537
<b>Dehumidifying</b>	Kg/h	1,8	
<b>Degree of protection (IN) / (OUT)</b>	(IP)	IPX0/IPX4	
<b>Class of electric protection (IN) / (OUT)</b>	Class I / Class II	I/I	
<b>Max. input consumption</b>	W	3000	
<b>Max. current</b>	A	14	
<b>Compressor</b>	Model	C-6RZ146H3BAF	
	Type	Rotary	
	Brand	SANYO	
<b>Indoor</b>	Indoor Air Circulation	m <sup>3</sup> /h	1100
	Indoor Noise Level dB	dB(A)	58/52/48/44/41
	Net Dimension	mm	1100×333×222
	Packing Dimension	mm	1165×405×295
	Net Weight / Gross Weight	Kg	147/17
<b>Outdoor</b>	Outdoor Noise Level dB	dB(A)	68
	Net Dimension	mm	920×699×380
	Packing Dimension	mm	960×732×400
	Net Weight / Gross Weight	Kg	40/46
	Refrigerant Type		R32
	Refrigerant Weight	Kg	1,11
	GWP		675
	tCO <sub>2</sub> eq.		0,75
<b>Max. Discharge / Max. Suction pressure</b>	Mpa	4.3/2.5	
<b>Refrigerant piping</b>	Liquid side / Gas side / Length	mm	Dg4/Dg8(1/4-1/2)
	Max. refrigerant pipe length / Max. difference in level	m	25/10