



Features

7-Fan Speed: Mute/Low/Low-Mid/Mid/Mid-High/High/Turbo, 5-Fan Speed: Mute/Low/Mid/High/Turbo, Turbo Mode, Anti-cold Air, Mute Mode, 8°C heating, I Feel, Low Temperature Cooling (-15°C), Comfortable Cooling, Independent Dehumidification, Holder RC, Auto Mode, Display On/Off, Smart Airflow, Rapid Cooling and Rapid Heating, Intelligent Defrost, Emergency Button, Rust Proof, Wide Voltage Range Start-up, Children Lock, Cooling at 53°C, Refrigerant Leakage Detection, Compressor Preheating, Auto-restart, Self-diagnosis, Backlight Display remote control, Louver Position Memory, Dual Drainage, Easy-washable Filter, I Set, Hidden Display, Self-cleaning, Self-cleaning (Outdoor unit), Sleep Mode, ECO, Timer, AI Energy Saving 2.0

Capacity		9000BTU	
Rated volt and frequency		V/Hz 220-240V~/50HZ	
Mode		Cooling	Heating
Rated capacity	W	2620(940~3300)	2700(1000~3810)
Power input	W	811(240~1380)	726(290~1720)
Current input	A	5.4(1.2~8.0)	4.8(1.5~9.0)
SEER / Energy Class		6,4 A++	/
SCOP / Energy Class - average		/	4,0/A+
SCOP / Energy Class - warmer		/	5,1/A+++
Operating range (°C)	°C	15-52°C	-20-30°C
Energy consumption (per year, based on standard test results)	kWh	143	/
Energy consumption (per year, based on standard test results) - average	kWh	/	770
Energy consumption (per year, based on standard test results) - warmer	kWh	/	687
Dehumidifying	Kg/h	2	
Degree of protection (IN) / (OUT)	(IP)	IPX0/IPX4	
Class of electric protection (IN) / (OUT)	Class I / Class II	I/I	
Max. input consumption	W	1720	
Max. current	A	9	
Compressor	Model	KSN89D28UDZW31	
	Type	Rotary	
	Brand	GMCC	
Indoor	Indoor Air Circulation	m ³ /h	570
	Indoor Noise Level dB	dB(A)	53/49/46/43/39/35/32
	Net Dimension	mm	778×272×192
	Packing Dimension	mm	840×335×255
	Net Weight / Gross Weight	Kg	7,3/9,5
Outdoor	Outdoor Noise Level dB	dB(A)	62
	Net Dimension	mm	712×459×276
	Packing Dimension	mm	765×481×310
	Net Weight / Gross Weight	Kg	20/22
	Refrigerant Type		R32
	Refrigerant Weight	Kg	0,52
	GWP		675
	tCO ₂ eq.		0,35
	Max. Discharge / Max. Suction pressure	Mpa	4.3/2.5
Refrigerant piping	Liquid side / Gas side / Length	mm	Dg4/Dg8(1/4-3/8)
	Max. refrigerant pipe length / Max. difference in level	m	25/10