



Features

7-Fan Speed: Mute/Low/Low-Mid/Mid/Mid-High/High/Turbo, 5-Fan Speed: Mute/Low/Mid/High/Turbo, Turbo Mode, Anti-cold Air, Mute Mode, 8°C heating, I Feel, Low Temperature Cooling (-15°C), Comfortable Cooling, Independent Dehumidification, Holder RC, Auto Mode, Display On/Off, Smart Airflow, Rapid Cooling and Rapid Heating, Intelligent Defrost, Emergency Button, Rust Proof, Wide Voltage Range Start-up, Children Lock, Cooling at 53°C, Refrigerant Leakage Detection, Compressor Preheating, Auto-restart, Self-diagnosis, Backlight Display remote control, Louver Position Memory, Dual Drainage, Easy-washable Filter, I Set, Hidden Display, Self-cleaning, Self-cleaning (Outdoor unit), Sleep Mode, ECO, Timer, AI Energy Saving 2.0, Wi Fi, Ionizer Filter, 4D Air Flow, Horizontal Swing

Capacity			12000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			Cooling
Rated capacity		W	3400(1000~3770)
Power input		W	1130(290~1500)
Current input		A	5.8(1.5~9.0)
SEER / Energy Class			6,1 A++
SCOP / Energy Class - average			/
SCOP / Energy Class - warmer			4,0/A+
Operating range (°C)		°C	15-52°C
Energy consumption (per year, based on standard test results)		kWh	196
Energy consumption (per year, based on standard test results) - average		kWh	/
Energy consumption (per year, based on standard test results) - warmer		kWh	770
Dehumidifying		Kg/h	1
Degree of protection (IN) / (OUT)		(IP)	IPX0/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	1720
Max. current		A	10
Compressor	Model		KSN89D28UDZW31
	Type		Rotary
	Brand		GMCC
Indoor	Indoor Air Circulation	m³/h	570
	Indoor Noise Level dB	dB(A)	53/49/46/43/39/35/32
	Net Dimension	mm	778×272×192
	Packing Dimension	mm	840×335×255
	Net Weight / Gross Weight	Kg	7,3/9,5
Outdoor	Outdoor Noise Level dB	dB(A)	62
	Net Dimension	mm	712×459×276
	Packing Dimension	mm	765×481×310
	Net Weight / Gross Weight	Kg	20/22
	Refrigerant Type		R32
	Refrigerant Weight	Kg	0,52
	GWP		675
	tCO ₂ eq.		0,35
	Max. Discharge / Max. Suction pressure	Mpa	4.3/2.5
	Liquid side / Gas side / Length	mm	Dg4/Dg8(1/4-3/8)
Refrigerant piping		Max. refrigerant pipe length / Max. difference in level	m
			25/10